



# Cloverdale Paint

 Canadian Owned & Operated

# GUARDIAN

## PREMIUM EXTERIOR FINISHES

Cloverdale Paint's Guardian line is a highly cross-linked 100% acrylic coating with exceptional application and performance.

- Available in Flat, Satin, Semi-Gloss Finishes
- Self-priming to most surfaces with excellent flexibility
- Best early water resistance in its class
- Low VOC and low temperature application
- Highly cross-linked film with excellent weathering, dirt, and mildew resistance
- Fortified with X-Link Technology for extended painting season



**Cloverdale Paint**

[www.cloverdalepaint.com](http://www.cloverdalepaint.com) 

Providing quality products and exceptional service to professional painters since 1933 • [www.cloverdalepaint.com](http://www.cloverdalepaint.com)



# GUARDIAN

Guardian is an ultra-premium, 100% acrylic exterior finish designed to deliver the highest level of protection. With superior adhesion, flexibility, weathering and self-priming capabilities, this coating delivers a barrier that will repel dirt and debris and reduce mildew growth to extend the life of the coating.



Fortified with X-Link Technology, this coating has exceptional early water resistance and low temperature capabilities which will allow you to extend your painting season knowing that this coating will withstand the negative impacts of early moisture exposure, high humidity, and cool overnight curing conditions. This product has excellent hide, flow and leveling properties that makes it an ideal choice for both DIY and professional applicators.

Approved under Master Painter's Institute category #10 for GL1 Flat, #11 for GL5 Semi-Gloss, and #15 for GL3 Satin finishes.

## Guardian Product Information

For more detailed information, refer to the Technical Data Sheet, available at [www.cloverdalepaint.com](http://www.cloverdalepaint.com)

### Solids by Volume

Product	SKU Codes	Volume Solids
Flat	02603	36.5%
Satin	02703	36%
Semi-Gloss	02803	35%

### Gloss Level

Product	Level
Flat	GL 1
Satin	GL 3
Semi-Gloss	GL 5

### V.O.C. Rating (g/L)

Product	Base	VOC
Flat	White, Deep, Neutral	< 50 g/L
Satin	White, Deep, Neutral	< 50 g/L
Semi-Gloss	White, Deep, Neutral	< 50 g/L

### Practical Spread Rate (ft<sup>2</sup> / gallon)

Product	Spread Rate
Flat	290 - 390
Satin	280 - 375
Semi-Gloss	350 - 450

### Dry Time at 77°F and 50% Relative Humidity

Product	Tack Free	Re-Coat
Flat	1 hour	4 hours
Satin	1 hour	4 hours
Semi-Gloss	1 hour	6 hours

### Thinning

Not normally recommended. 10% clean water for spray applications.

### Clean Up

Clean tools and equipment with warm, soapy water. Contact your local municipality for disposal instructions.

Cloverdale Paint stores and authorized dealers

