



Cloverdale Paint

 Canadian Owned & Operated

ecologic™

The Logical Environmental Choice.

ColourCoat

Tough, durable and high hiding for bright, vivid accent colours in a low odour low VOC formulation. Available in a low-sheen eggshell or low sheen semi-gloss for higher durability.

- Recommended for use where bright, vivid colours are required in a high performance coating.
- Suitable for use on interior accent walls, signs, graphics or trim for application by brush roll or spray.
- EcoLogic® ColourCoat is optimized to provide maximum hiding levels yet retain a high degree of tinting range to achieve a range of standard and custom colours.

EcoLogic ColourCoat Series are high performance coatings formulated with the highest possible opacity for clean bright accent colours.

GLOSS LEVEL 2

70631 YELLOW BASE
70632 BLUE BASE
70633 RED BASE

GLOSS LEVEL 4

70641 YELLOW BASE
70642 BLUE BASE
70643 RED BASE



Cloverdale Paint

www.cloverdalepaint.com

Providing quality products and exceptional service to professional painters since 1933 • www.cloverdalepaint.com

ColourCoat

PRODUCT FEATURES

EcoLogic ColourCoat is formulated as a high-hiding high opacity accent base for bright, clean accent colours. Suitable for use on interior accent walls, signs, graphics, or trim for application by brush or roller. EcoLogic ColourCoat is optimized to provide maximum hiding levels yet retain a high degree of tinting range to achieve a wide range of Cloverdale and custom colours.

- High hiding - even in bright clean accent colours
- Low odour, low VOC, excellent application properties
- Interior / exterior performance
- Tough, durable, mar resistant coating.
- Level 2 low gloss finish hides substrate irregularities.
- Contains an Agriculture Canada approved mildewcide



EcoLogic® ColourCoat®

Product Information

For more detailed information, refer to the Technical Data Sheet, available at www.cloverdalepaint.com

Solids & Density

SKU Code	Volume	Weight
70633	37%	39%

Sheen Levels

Gloss @ 60°	Sheen @ 85°	Gloss Level
10 units	10-35 units	GL2

VOC Rating (g/L)

Base	VOC
Yellow base (70631)	< 135 (g/L)
Red Base (70633)	< 120 (g/L)
Blue Base (70632)	< 135 (g/L)

Practical Spread Rate (ft² / gallon)

Spread Rate

190 - 320 ft²/gal (4.6 - 7.9 m²/L)

Dry Time at 77°F and 50% Relative Humidity

To Touch	Re-Coat
30 min	6 hours

Thinning

Not normally recommended, sparingly with water for spray applications.

Tools & Techniques

Clean tools and equipment with warm, soapy water. Contact your local municipality for disposal instructions.

Cloverdale Paint stores and authorized dealers

