

OUR TOUGHEST AND MOST VERSATILE COATING

MultiMaster

MULTIMASTER



Universal Finish!

One Coating for Most Applications

MultiMaster™ is a universal, self-priming finish with exceptional adhesion and toughness designed for both interior and exterior applications. Its waterborne formula provides a fast-drying, exceptionally hard-wearing finish for both Commercial and DIY applications.

DESCRIPTION

MultiMaster is a Water-borne Acrylic Polyurethane Enamel designed for both interior and exterior applications. Formulated with our VST (Variable Substrate Technology), this universal coating provides both functionality and aesthetic value in a low odour, non-flammable formulation. This quick dry product can be applied by brush, roll or spray with excellent flow and leveling. This hard wearing, non-blocking product it can be used for both commercial and DIY applications and complies with Government of Canada Emission regulations under category 52.

RECOMMENDED USES

Ideal for use on ferrous and non-ferrous surfaces. Designed for use on interior and exterior wood, concrete and plastics. Ideal for DIY and Commercial Maintenance programs.

FEATURES

- Exceptional adhesion and block resistance
- Self-priming to most surfaces
- Fortified with urethane for toughness and durability
- Applies like an alkyd with excellent flow and leveling over difficult surfaces
- Water clean-up



Product Information

For more detailed information, refer to the Technical Data Sheet, available at www.cloverdalepaint.com

Solids by Volume

Products	Codes	Volume Solids
Satin	71453	36%
Semi-Gloss	71423	34%

Sheen Levels

Products	Gloss@ 60°	Gloss Level
Satin (GL3)	20 - 25 units	GL3
Semi-Gloss (GL5)	55 - 60 units	GL5

VOC Rating (g/L)

Products	Base	VOC
ALL	ALL	< 95 g/L

Practical Spread Rate (ft² / gallon)

Products	Spread Rate
Satin	202 - 275 ft ²
Semi-Gloss	272 - 363 ft ²

Dry Times at 25°C, 50% Relative Humidity

Products	Tack Free	Re-Coat
ALL	30 minutes	2 hours

Cloverdale Paint Store or Authorized Dealer:

#SAI0061 08/18

