



Cloverdale Paint

 Canadian Owned & Operated

WEATHER^{ONE}

Exterior CoverCoat Series

Cloverdale Paint's exterior WeatherOne CoverCoat series is a 100% waterborne acrylic line of premium coatings designed for multiple exterior applications. WeatherOne CoverCoat is available in flat, satin and semi-gloss finishes providing beautiful and durable exterior protection.

- 100% acrylic for exterior durability & colour retention
- High moisture permeability provides breathable protection against peeling and blistering
- Superior mould & mildew resistance
- Low temperature applications*
May be applied at air temperatures as low as 2°C (35° F)

*Temperatures should remain above 2°C (35°F) during "re-coat" window dry times. See Technical Data Sheet for application instructions

Meets and exceeds MPI (Master Painter Institute) certification standards


WeatherOne CoverCoat 02203 Flat MPI #10

WeatherOne CoverCoat 02010 Satin MPI #15

WeatherOne CoverCoat 02123 Semi-Gloss MPI #11



Cloverdale Paint

www.cloverdalepaint.com 

Providing quality products and exceptional service to professional painters since 1933

WEATHERONE®

Exterior CoverCoat Series

WeatherOne CoverCoat is ideal for multiple exterior applications. Use on primed wood, fiber and cement board siding, stucco, concrete and masonry substrates. WeatherOne CoverCoat has excellent adhesion to properly prepared galvanized and aluminum down spouts, gutters and flashing.

WeatherOne CoverCoat may also be used to rejuvenate old and faded vinyl siding*. **Painting dark colours on vinyl siding is not recommended as heat absorption may cause the vinyl to warp and ripple.**



WeatherOne CoverCoat may be applied in low temperatures extending the window for exterior painting projects.

WeatherOne CoverCoat is designed with high flexibility and moisture permeability providing breathable protection against blistering and peeling.

WeatherOne CoverCoat adheres to multiple exterior surfaces including wood, fiber and cement board siding, galvanized, aluminum and other properly prepared metal flashings and trims. This enables the applicator to use a single product on several exterior substrates that may potentially be on the same project.

***Speak with a Cloverdale Paint Representative regarding colours and suitability of WeatherOne CoverCoat on vinyl siding.**

Meets and exceeds MPI (Master Painter Institute) certification standards

WeatherOne CoverCoat 02203 Flat MPI #10

WeatherOne CoverCoat 02010 Satin MPI #15

WeatherOne CoverCoat 02123 Semi-Gloss MPI #11

For more detailed information, refer to the Technical Data Sheet available at www.cloverdalepaint.com

WeatherOne® CoverCoat Product Information

Solids by Volume

Product	SKU Codes	Volume Solids
Flat	0220-Series	36%
Satin	0201-Series	35%
Semi-Gloss	0212-Series	36%

Sheen Levels

Product	Gloss @60°	Gloss Level
Flat	< 10 Units	GL1
Satin	< 35 Units	GL3-4
Semi-Gloss	35 - 70 Units	GL5

VOC Rating (g/L)

Product	Base	VOC
Flat	White	< 100
Satin	White	< 150
Semi-Gloss	White	< 140

Practical Spread Rate (ft² / gallon)

Product	Spread Rate
Flat	290 - 390 ft²
Satin	280 - 370 ft²
Semi-Gloss	350 - 450 ft²

Dry Times at 20°C, 50% Relative Humidity

Product	To Touch	Re-Coat	Thorough Dry
Flat	1 hour	4 hours	24 hours?
Satin	45 minutes	6 hours	24 hours?
Semi-Gloss	45 minutes	8 hours	24 hours?

Thinning

Not normally recommended.
Up to 10% with clean water for spray applications.

Clean-up

Clean application equipment with warm, soapy water.

Cloverdale Paint Store or Authorized Dealer:

