

TIMBERLOX

Interior waterborne varnishes that feature good hardness adhesion and durability. Timberlox 593 and 470 Series Varnishes are non-flammable, environmentally friendly with very low odour levels. 59324 Gloss Varnish can be used for exterior.



#593 SERIES

WATERBORNE ALKYD VARNISH

#470 SERIES

WATERBORNE POLYCARBONATE VARNISH

T E C H N I C A L S P E C I F I C A T I O N S

593 Series Waterborne

Alkyd Varnish

Good hardness, adhesion and durability. Non-flammable resistant to household chemicals. Very low odour and VOC levels. Cleans up with soap and water.

INTENDED USES

On all interior and exterior wood furniture, shelving cabinets, doors and other woodwork. This product is not designed as a floor coating.

CERTIFICATIONS

MPI # 128, 129 and 130
Environment Canada VOC compliant.
Less than 100 g/L

FINISHES

59304 Low Lustre, 59314 Satin, 59324 Gloss, 59334 Semi Gloss

BASES AVAILABLE

N/A

V.O.C.

Less than 100 g/L

SOLIDS

30% by volume
32% by weight

FILM THICKNESS (per coat)

Wet: 3.0 - 4.0 mils
Dry: 0.9 - 1.2 mils

DRY TIME

Tack Free: 1 hour
Re-Coat: 2 hours

SPREAD / COVERAGE

440 ft²/gal (10.8 m²/L)

TOOLS & TECHNIQUES

Brush, roll or spray.
Airless tip sizes: 0.007" - 0.011"

470 Series Waterborne

Polycarbonate Varnish

Non-yellowing, excellent abrasion and chemical resistance, low odour, crystal clear finish. Non-flammable and resistant to hot and cold water, household chemicals and alcohol. Environmentally friendly, soap and water clean-up and have much faster dry times than solvent based products.

INTENDED USES

Interior wood or concrete floors, wood furniture, shelving, cabinets, doors, trim and other woodwork.

CERTIFICATIONS

Environment Canada VOC compliant.
Less than 320 g/L

FINISHES

47014 Satin, 47024 Gloss

BASES AVAILABLE

N/A

V.O.C.

Less than 320 g/L

SOLIDS

26% by volume
28% by weight

FILM THICKNESS (per coat)

Wet: 4.0 - 6.0 mils
Dry: 1.0 - 1.5 mils

DRY TIME

Tack Free: 30 minutes
Re-Coat: 2 hours

SPREAD / COVERAGE

267 - 400 ft²/gal (6.6 - 10.0 m²/L)

TOOLS & TECHNIQUES

Brush, roll or spray
Airless tip sizes: 0.007" - 0.011"

PRODUCT FEATURES

Timberlox VOC Compliant Varnishes are low VOC, low odour fast drying varnishes that are environmentally friendly products with soap and water clean up. These products meet the Environment Canada National Volatile Organic Compound Emission Standards for Architectural Varnishes.



Cloverdale Paint stores and authorized dealers

For the most up-to-date technical information and MSDS sheets, visit our web site at www.cloverdalepaint.com

MANUFACTURED BY



6950 King George Boulevard

Surrey, BC, Canada

V3W 4Z1

www.cloverdalepaint.com

#86333

03/12