

## SECTION 1: Identification

### 1.1. Product identifier

Product form	: Mixture
Product name	: INTERIOR SEMI-GLOSS ACRYLIC LATEX NEUTRAL BASE-PREMIUM CLASSIC
Product code	: 01124
Product group	: Trade product

### 1.2. Recommended use and restrictions on use

Recommended use	: Coatings and paints
-----------------	-----------------------

### 1.3. Supplier

Cloverdale Paint Inc.  
400- 2630 Croydon Drive  
V3Z 6T3 SURREY - CANADA  
T 1-(604)-596-6261  
[www.cloverdalepaint.com](http://www.cloverdalepaint.com)

### 1.4. Emergency telephone number

Emergency number	: 613-996-6666
------------------	----------------

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

#### Classification (GHS-CA)

Skin sensitisation, Category 1	H317
Carcinogenicity, Category 1	H350
Full text of H statements : see section 16	

### 2.2. GHS Label elements, including precautionary statements

#### GHS-CA labelling

Hazard pictograms (GHS-CA)



Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) : H317 - May cause an allergic skin reaction.  
H350 - May cause cancer.

Precautionary statements (GHS-CA) : P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P261 - Avoid breathing mist, vapours, spray.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P280 - Wear eye protection, face protection, protective gloves, protective clothing.  
P302+P352 - IF ON SKIN: Wash with plenty of soap & water.  
P308+P313 - IF exposed or concerned: Get medical advice/attention.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS-CA)

1.78% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
1.78% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# INTERIOR SEMI-GLOSS ACRYLIC LATEX NEUTRAL BASE-PREMIUM CLASSIC

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
Latex Resin			55.1	Skin Sens. 1, H317
TEXANOL/UCAR FILMER IBT	Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol / Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol / Propionic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol / Texanol / 2,2,4-Trimethyl-1,3-pentanediol isobutyrate / 2,2,4-Trimethyl-1,3-pentanediol monoisobutyrate / Trimethyl pentanediol monoisobutyrate / Isobutyric acid, monoester with 2,2,4-trimethyl-1,3-pentanediol / 2,2,4-Trimethyl-1,3-pentanediol mono(2-methylpropanoate) / 2,2,4-Trimethyl-1,3-pentanediol 2-methylpropanoate / 2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate) / Trimethyl hydroxypentyl isobutyrate	(CAS-No.) 25265-77-4	1.8	Acute Tox. 3 (Inhalation:vapour), H331 Aquatic Acute 3, H402
ETHYLENE GLYCOL	1,2-Dihydroxyethane / Ethane-1,2-diol / 1,2-Ethandiol / Ethandiol / Dowtherm 4000 / GLYCOL / Glycol / Monoethylene glycol / Ethandiol	(CAS-No.) 107-21-1	1	Acute Tox. 4 (Oral), H302 STOT SE 3, H335
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	Petroleum distillates, solvent dewaxed heavy paraffinic / Distillates (petroleum), solvent-dewaxed heavy paraffinic / Paraffin oil / Distillates, petroleum, solvent dewaxed heavy paraffinic / Oils, paraffinic, heavy, solvent-dewaxed / Distillates, petroleum, solvent-dewaxed heavy paraffinic (A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20-50 and produces a finished oil with a viscosity not less than 100 SUS at 100°F.)	(CAS-No.) 64742-65-0	0.6	Carc. 1B, H350

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: May cause an allergic skin reaction.
-------------------------------------	--

### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

### 5.2. Unsuitable extinguishing media

No additional information available

### 5.3. Specific hazards arising from the hazardous product

No additional information available

# INTERIOR SEMI-GLOSS ACRYLIC LATEX NEUTRAL BASE-PREMIUM CLASSIC

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

### 6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes. Avoid breathing mist, vapours, spray.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

ETHYLENE GLYCOL (107-21-1)		
USA - ACGIH	ACGIH TWA (ppm)	25 ppm (vapor fraction)
USA - ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter, aerosol only)
USA - ACGIH	ACGIH STEL (ppm)	50 ppm (vapor fraction)
Canada (Quebec)	PLAFOND (mg/m <sup>3</sup> )	127 mg/m <sup>3</sup> (mist and vapour)
Canada (Quebec)	PLAFOND (ppm)	50 ppm (mist and vapour)
Alberta	OEL Ceiling (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
British Columbia	OEL Ceiling (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup> (aerosol)
British Columbia	OEL Ceiling (ppm)	50 ppm (vapour)
British Columbia	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> (particulate)
British Columbia	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (particulate)
Manitoba	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter, aerosol only)
Manitoba	OEL STEL (ppm)	50 ppm (vapor fraction)
Manitoba	OEL TWA (ppm)	25 ppm (vapor fraction)
New Brunswick	OEL Ceiling (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup> (aerosol)
New Foundland & Labrador	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter, aerosol only)
New Foundland & Labrador	OEL STEL (ppm)	50 ppm (vapor fraction)
New Foundland & Labrador	OEL TWA (ppm)	25 ppm (vapor fraction)
Nova Scotia	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter, aerosol only)
Nova Scotia	OEL STEL (ppm)	50 ppm (vapor fraction)
Nova Scotia	OEL TWA (ppm)	25 ppm (vapor fraction)
Nunavut	OEL Ceiling (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup> (aerosol)
Northwest Territories	OEL Ceiling (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup> (aerosol)
Ontario	OEL Ceiling (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup> (aerosol only)

# INTERIOR SEMI-GLOSS ACRYLIC LATEX NEUTRAL BASE-PREMIUM CLASSIC

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### ETHYLENE GLYCOL (107-21-1)

Prince Edward Island	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter, aerosol only)
Prince Edward Island	OEL STEL (ppm)	50 ppm (vapor fraction)
Prince Edward Island	OEL TWA (ppm)	25 ppm (vapor fraction)
Saskatchewan	OEL Ceiling (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup> (aerosol)
Yukon	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> (particulate)
Yukon	OEL STEL (ppm)	10 ppm (particulate)
Yukon	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (particulate)
Yukon	OEL TWA (ppm)	100 ppm (vapour)

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: clear
Odour	: Amine-like
Odour threshold	: No data available
pH	: 8.5 - 9.5
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: ≈ 0 °C
Boiling point	: ≈ 100 °C
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Specific gravity	: 1.07
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content : < 125 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

# INTERIOR SEMI-GLOSS ACRYLIC LATEX NEUTRAL BASE-PREMIUM CLASSIC

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Unknown acute toxicity (GHS-CA)	1.78% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 1.78% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
---------------------------------	--

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (64742-65-0)	
LD50 oral rat	> 15000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 2400 mg/m <sup>3</sup> (Exposure time: 4 h)

ETHYLENE GLYCOL (107-21-1)	
LD50 oral rat	4700 mg/kg
LD50 dermal rat	10600 mg/kg

TEXANOL/UCAR FILMER IBT (25265-77-4)	
LD50 oral rat	3200 mg/kg
LD50 dermal rat	> 15200 mg/kg
LC50 inhalation rat (mg/l)	> 3.55 mg/l (Exposure time: 6 h)

Skin corrosion/irritation	: Not classified pH: 8.5 - 9.5
Serious eye damage/irritation	: Not classified pH: 8.5 - 9.5
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
-------------------	---

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (64742-65-0)	
LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

ETHYLENE GLYCOL (107-21-1)	
LC50 fish 1	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
LC50 fish 2	14 - 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)

TEXANOL/UCAR FILMER IBT (25265-77-4)	
LC50 fish 1	30 mg/l (Exposure time: 96 h - Species: Pimephales promelas)

#### 12.2. Persistence and degradability

No additional information available

# INTERIOR SEMI-GLOSS ACRYLIC LATEX NEUTRAL BASE-PREMIUM CLASSIC

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 12.3. Bioaccumulative potential

#### ETHYLENE GLYCOL (107-21-1)

Log Pow	-1.93
---------	-------

#### TEXANOL/UCAR FILMER IBT (25265-77-4)

Log Pow	3.47 (at 25 °C)
---------	-----------------

### 12.4. Mobility in soil

#### ETHYLENE GLYCOL (107-21-1)

Log Pow	-1.93
---------	-------

#### TEXANOL/UCAR FILMER IBT (25265-77-4)

Log Pow	3.47 (at 25 °C)
---------	-----------------

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### 14.1. Basic shipping description

In accordance with TDG

#### Transportation of Dangerous Goods

Not regulated for transport

### 14.2. Transport information/DOT

#### Department of Transport

Not regulated for transport

### 14.3. Air and sea transport

#### IMDG

Not regulated for transport

#### IATA

Not regulated for transport

## SECTION 15: Regulatory information

### 15.1. National regulations

#### DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (64742-65-0)

Listed on the Canadian DSL (Domestic Substances List)

#### ETHYLENE GLYCOL (107-21-1)

Listed on the Canadian DSL (Domestic Substances List)

#### TEXANOL/UCAR FILMER IBT (25265-77-4)

Listed on the Canadian DSL (Domestic Substances List)

### 15.2. International regulations

#### DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (64742-65-0)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Latex Resin

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

# INTERIOR SEMI-GLOSS ACRYLIC LATEX NEUTRAL BASE-PREMIUM CLASSIC

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### ETHYLENE GLYCOL (107-21-1)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Japanese ISHL (Industrial Safety and Health Law)  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### TEXANOL/UCAR FILMER IBT (25265-77-4)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)  
Listed on the Japanese ISHL (Industrial Safety and Health Law)  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

## SECTION 16: Other information

Date of issue : 06/12/2019

Full text of H-statements:

H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H402	Harmful to aquatic life

SDS Canada (GHS) - Cloverdale

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*