

INT/EXT WEATHERONE COVERCOAT FLAT BLACK LATEX

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 05/11/2017

Revision date: 05/23/2023

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Product name : INT/EXT WEATHERONE COVERCOAT FLAT BLACK LATEX
Product code : 02007
Product group : Trade product

1.2. Recommended use and restrictions on use

Recommended use : Coatings and paints

1.3. Supplier

Cloverdale Paint Inc.
400- 2630 Croydon Drive
V3Z 6T3 SURREY - CANADA
T 1-(604)-596-6261
www.cloverdalepaint.com

1.4. Emergency telephone number

Emergency number : 613-996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Carcinogenicity, H351
Category 2
Specific target organ H372
toxicity — Repeated
exposure, Category 1
Hazardous to the H402
aquatic environment —
Acute Hazard,
Category 3
Hazardous to the H412
aquatic environment —
Chronic Hazard,
Category 3

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA)



Signal word (GHS-CA)

: Danger

Hazard statements (GHS-CA)

: H351 - Suspected of causing cancer.
H372 - Causes damage to organs through prolonged or repeated exposure.
H402 - Harmful to aquatic life
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (GHS-CA)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe mist, vapours, spray.
P264 - Wash Skin thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P273 - Avoid release to the environment.
P280 - Wear eye protection, face protection, protective gloves, protective clothing.
P314 - Get medical advice/attention if you feel unwell.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

INT/EXT WEATHERONE COVERCOAT FLAT BLACK LATEX

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
TALC (CONTAINING NO ASBESTOS OR QUARTZ)	Talc / Magnesium silicate / Talc (containing no asbestos fibres) / Talc (containing no asbestos) / Talc not containing asbestiform fibres / Talc (nonasbestos form) / Talc (non-asbestos form) / Talc, containing no asbestos fibres / Talc, not containing asbestos / Talc, non-fibrous type / Talc, non fibrous / Talc (containing no asbestos fibres) / Non-asbestiform talc / Talc (not containing asbestos) / C.I. 77718 / TALC / Trimagnesium tetrasilicon undecaoxide hydrate / Talc, non-asbestiform / Talc, non-fibrous / Pigment White 26 / Magnesium silicate, hydrous / Talc, not containing mineral fibers (including asbestos)	(CAS-No.) 14807-96-6	1 - 5	STOT RE 1, H372
CARBON BLACK	C.I. 77266 / C.I. Pigment Black 6 / C.I. Pigment Black 7 / Carbon blacks / Lampblack / CI 77266 / Vegetable carbon / Microjet Black CW / Pigment Black 7 / Coal soot / Coal soots / Channel black / Bonjet Black CW / Carbon Black	(CAS-No.) 1333-86-4	0.5 - 1.5	Carc. 2, H351 Comb. Dust

Full text of hazard classes and H-statements : see section 16

Comments : Actual concentrations are withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.
First-aid measures general : IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

No additional information available

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

INT/EXT WEATHERONE COVERCOAT FLAT BLACK LATEX

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe mist, vapours, spray.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

INT/EXT WEATHERONE COVERCOAT FLAT BLACK LATEX		
USA - ACGIH	ACGIH TWA (mg/m³)	525 mg/m³ MINERAL SPIRITS
USA - ACGIH	ACGIH TWA (ppm)	100 ppm MINERAL SPIRITS
USA - OSHA	OSHA PEL (TWA) [1]	525 mg/m³ MINERAL SPIRITS
USA - OSHA	OSHA PEL (TWA) (ppm)	100 ppm MINERAL SPIRITS
CARBON BLACK (1333-86-4)		
USA - ACGIH	ACGIH TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
USA - OSHA	OSHA PEL (TWA) [1]	3.5 mg/m³
Canada (Quebec)	VEMP (mg/m³)	3.5 mg/m³
Alberta	OEL TWA (mg/m³)	3.5 mg/m³
British Columbia	OEL TWA (mg/m³)	3 mg/m³ (inhalable)
Manitoba	OEL TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m³)	3.5 mg/m³
New Foundland & Labrador	OEL TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
Nunavut	OEL STEL (mg/m³)	7 mg/m³
Nunavut	OEL TWA (mg/m³)	3.5 mg/m³
Northwest Territories	OEL STEL (mg/m³)	7 mg/m³
Northwest Territories	OEL TWA (mg/m³)	3.5 mg/m³
Ontario	OEL TWA (mg/m³)	3 mg/m³ (inhalable)
Prince Edward Island	OEL TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
Saskatchewan	OEL STEL (mg/m³)	7 mg/m³
Saskatchewan	OEL TWA (mg/m³)	3.5 mg/m³
Yukon	OEL STEL (mg/m³)	7 mg/m³
Yukon	OEL TWA (mg/m³)	3.5 mg/m³
TALC (CONTAINING NO ASBESTOS OR QUARTZ (14807-96-6)		
USA - ACGIH	ACGIH TWA (mg/m³)	2 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
Canada (Quebec)	VEMP (mg/m³)	3 mg/m³ (respirable dust)
Alberta	OEL TWA (mg/m³)	2 mg/m³ (respirable particulate)
British Columbia	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate)

INT/EXT WEATHERONE COVERCOAT FLAT BLACK LATEX

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

TALC (CONTAINING NO ASBESTOS OR QUARTZ (14807-96-6))

Manitoba	OEL TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-particulate matter, respirable particulate matter)
New Brunswick	OEL TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable fraction)
New Foundland & Labrador	OEL TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-particulate matter, respirable particulate matter)
Nova Scotia	OEL TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-particulate matter, respirable particulate matter)
Nunavut	OEL TWA (mg/m ³)	2 mg/m ³ (respirable fraction)
Northwest Territories	OEL TWA (mg/m ³)	2 mg/m ³ (respirable fraction)
Ontario	OEL TWA (mg/m ³)	2 mg/m ³ (containing no Asbestos and <1% Crystalline silica-respirable)
Prince Edward Island	OEL TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-particulate matter, respirable particulate matter)
Saskatchewan	OEL TWA (mg/m ³)	2 mg/m ³ (respirable fraction)
Yukon	OEL TWA (mg/m ³)	20 mppcf

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Black
Odour	: Amine-like
Odour threshold	: No data available
pH	: 8.5 - 9.5
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: ≈ 0 °C
Boiling point	: ≈ 100 °C
Flash point	: > 94 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Specific gravity	: 11.98
Density	: 9.98 lb/gal
Solubility	: No data available

INT/EXT WEATHERONE COVERCOAT FLAT BLACK LATEX

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Log Pow	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: < 50 g/l
-------------	------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

CARBON BLACK (1333-86-4)

LD50 oral rat	> 15400 mg/kg
Skin corrosion/irritation	: Not classified pH: 8.5 - 9.5
Serious eye damage/irritation	: Not classified pH: 8.5 - 9.5
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life. Harmful to aquatic life with long lasting effects.
Acute aquatic toxicity	: Harmful to aquatic life.
Chronic aquatic toxicity	: Harmful to aquatic life with long lasting effects.

TALC (CONTAINING NO ASBESTOS OR QUARTZ) (14807-96-6)

LC50 fish 1	> 100 g/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
BCF fish 1	(no known bioaccumulation)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

TALC (CONTAINING NO ASBESTOS OR QUARTZ) (14807-96-6)

BCF fish 1	(no known bioaccumulation)
------------	----------------------------

12.4. Mobility in soil

No additional information available

INT/EXT WEATHERONE COVERCOAT FLAT BLACK LATEX

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

Not regulated for transport

14.2. Transport information/DOT

Department of Transport

Not regulated for transport

14.3. Air and sea transport

IMDG

Not regulated for transport

IATA

Proper Shipping Name (IATA) : Flammable liquid, n.o.s.

SECTION 15: Regulatory information

15.1. National regulations

CARBON BLACK (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

TALC (CONTAINING NO ASBESTOS OR QUARTZ (14807-96-6)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

CARBON BLACK (1333-86-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on ELINCS (European List of Notified Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

TALC (CONTAINING NO ASBESTOS OR QUARTZ (14807-96-6)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16: Other information

Date of issue : 05/11/2017

Revision date : 05/23/2023

Full text of H-statements:

H351 Suspected of causing cancer.

INT/EXT WEATHERONE COVERCOAT FLAT BLACK LATEX

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

H372	Causes damage to organs through prolonged or repeated exposure.
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects.

SDS Canada (GHS)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product