

**SECTION 1: Identification****1.1. Product identifier**

Product form : Mixture
Product name : LATEX BLOCK FILLER WHITE
Product code : 05740
Product group : Trade product

1.2. Recommended use and restrictions on use

Recommended use : Coatings and paints

1.3. Supplier

Cloverdale Paint Inc.
400- 2630 Croydon Drive
V3Z 6T3 SURREY - CANADA
T 1-(604)-596-6261
www.cloverdalepaint.com

1.4. Emergency telephone number

Emergency number : 613-996-6666

SECTION 2: Hazard identification**2.1. Classification of the substance or mixture****Classification (GHS-CA)**

Carcinogenicity, Category 1 H350
Specific target organ toxicity — Repeated H372
exposure, Category 1
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements**GHS-CA labelling**

Hazard pictograms (GHS-CA) :



GHS08

Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) : H350 - May cause cancer.
H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS-CA) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe mist, vapours, spray.
P264 - Wash Skin thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P280 - Wear eye protection, face protection, protective gloves, protective clothing.
P314 - Get medical advice/attention if you feel unwell.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

LATEX BLOCK FILLER WHITE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
CALCIUM CARBONATE	Chalk / Limestone (A noncombustible solid characteristic of sedimentary rock. It consists primarily of calcium carbonate.) / Natural calcium carbonate / Marble / Calcium carbonate / Limestone (sedimentary rock) / Calcite / Limestone ground / Acetate, 4-methyl-2-propyl-2H-tetrahydropyran-4-yl	(CAS-No.) 1317-65-3	23.4	Carc. 1A, H350 STOT RE 1, H372
TALC	Talc / Magnesium silicate / Talc (containing no asbestos fibers) / Talc (containing no asbestos) / Talc (nonasbestos form) / Talc not containing asbestiform fibres / Talc, not containing asbestos / Talc, containing no asbestos fibres / Talc (non-asbestos form) / Talc, non-fibrous type / Talc, non fibrous / Talc (nonasbestiform) / Talc (containing no asbestos fibres) / Non-asbestiform talc / Talc (not containing asbestos) / C.I. 77718 / TALC / Talc, non-asbestos form / Trimagnesium tetrasilicon undecaoxide hydrate / Talc, fibrous / Talc, non-asbestiform / Talc, non-fibrous / Pigment White 26 / Magnesium silicate, hydrous	(CAS-No.) 14807-96-6	3.3	STOT RE 1, H372 Comb. Dust
TITANIUM DIOXIDE	C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO ₂) / CI 77891 / Titanium(IV) oxide / C.I. Pigment White 7 / Pigment White 6 / Titanium dioxide nanoparticles / TITANIUM DIOXIDE / Titanium oxide	(CAS-No.) 13463-67-7	1.8	Carc. 2, H351
ALIPHATIC PETROLEUM DISTILLATES	Petroleum distillates, solvent-refined heavy paraffinic / Distillates (petroleum), solvent refined, heavy paraffinic / Distillates, petroleum, solvent refined heavy paraffinic / Distillates (petroleum), solvent-refined heavy paraffinic / Paraffin oil / Distillates (petroleum) solvent-refined heavy paraffinic / Distillates (petroleum) solvent-refined heavy paraffinic; base oil - unspecified / Distillates, petroleum, solvent-refined heavy paraffinic (A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20-50 and produces a finish oil with a viscosity of at least 100 SUS at 100°F (19cSt at 40°C).) / Petroleum distillate solvent refined heavy paraffinic	(CAS-No.) 64741-88-4	0.1	Carc. 1B, H350

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
 First-aid measures after skin contact : Wash skin with plenty of water.
 First-aid measures after eye contact : Rinse eyes with water as a precaution.
 First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.
 First-aid measures general : IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

LATEX BLOCK FILLER WHITE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

No additional information available

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe mist, vapours, spray.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

TITANIUM DIOXIDE (13463-67-7)		
USA - ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
Canada (Quebec)	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust)
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (total dust)
Manitoba	OEL TWA (mg/m ³)	10 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
New Foundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³
Ontario	OEL TWA (mg/m ³)	10 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³

LATEX BLOCK FILLER WHITE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

TITANIUM DIOXIDE (13463-67-7)		
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³
Yukon	OEL STEL (mg/m³)	20 mg/m³
Yukon	OEL TWA (mg/m³)	30 mppcf
TALC (14807-96-6)		
USA - ACGIH	ACGIH TWA (mg/m³)	2 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
Canada (Quebec)	VEMP (mg/m³)	3 mg/m³ (respirable dust)
Alberta	OEL TWA (mg/m³)	2 mg/m³ (respirable particulate)
British Columbia	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate)
Manitoba	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate matter)
New Brunswick	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable fraction)
New Foundland & Labrador	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate matter)
Nunavut	OEL TWA (mg/m³)	2 mg/m³ (respirable fraction)
Northwest Territories	OEL TWA (mg/m³)	2 mg/m³ (respirable fraction)
Ontario	OEL TWA (mg/m³)	2 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable)
Prince Edward Island	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate matter)
Saskatchewan	OEL TWA (mg/m³)	2 mg/m³ (respirable fraction)
Yukon	OEL TWA (mg/m³)	20 mppcf
CALCIUM CARBONATE (1317-65-3)		
USA - OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)
Canada (Quebec)	VEMP (mg/m³)	10 mg/m³ (Limestone, containing no Asbestos and <1% Crystalline silica-total dust)
Alberta	OEL TWA (mg/m³)	10 mg/m³
British Columbia	OEL STEL (mg/m³)	20 mg/m³ (total dust)
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (total dust)
New Brunswick	OEL TWA (mg/m³)	10 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica)
Nunavut	OEL STEL (mg/m³)	20 mg/m³
Nunavut	OEL TWA (mg/m³)	10 mg/m³
Northwest Territories	OEL STEL (mg/m³)	20 mg/m³
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³
Yukon	OEL STEL (mg/m³)	20 mg/m³
Yukon	OEL TWA (mg/m³)	30 mppcf

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

LATEX BLOCK FILLER WHITE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Mixture contains one or more component(s) which have the following colour(s): Colourless clear Black white Yellow red brown Green Blue brown
Odour	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: ammonia-like sweet to sharp
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Specific gravity	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

ALIPHATIC PETROLEUM DISTILLATES (64741-88-4)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5530 mg/m ³ (Exposure time: 4 h)

LATEX BLOCK FILLER WHITE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

TITANIUM DIOXIDE (13463-67-7)

LD50 oral rat	> 10000 mg/kg
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

ALIPHATIC PETROLEUM DISTILLATES (64741-88-4)

LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

TALC (14807-96-6)

LC50 fish 1	> 100 g/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
-------------	--

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

TALC (14807-96-6)

BCF fish 1	(no known bioaccumulation)
------------	----------------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

Not regulated for transport

14.2. Transport information/DOT

Department of Transport

Not regulated for transport

14.3. Air and sea transport

IMDG

Not regulated for transport

IATA

Not regulated for transport

SECTION 15: Regulatory information

15.1. National regulations

LATEX BLOCK FILLER WHITE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

ALIPHATIC PETROLEUM DISTILLATES (64741-88-4)

Listed on the Canadian DSL (Domestic Substances List)

TITANIUM DIOXIDE (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

TALC (14807-96-6)

Listed on the Canadian DSL (Domestic Substances List)

CALCIUM CARBONATE (1317-65-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

15.2. International regulations

ALIPHATIC PETROLEUM DISTILLATES (64741-88-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

TITANIUM DIOXIDE (13463-67-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

TALC (14807-96-6)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

CALCIUM CARBONATE (1317-65-3)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

SECTION 16: Other information

Date of issue : 07/06/2018

Full text of H-statements:

H350	May cause cancer.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

LATEX BLOCK FILLER WHITE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product