

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Product name : FORMWORX WB CONCRETE STAIN WHITE BASE
Product code : 55503
Product group : Trade product

1.2. Recommended use and restrictions on use

Recommended use : Coatings and paints

1.3. Supplier

Cloverdale Paint Inc.
400- 2630 Croydon Drive
V3Z 6T3 SURREY - CANADA
T 1-(604)-596-6261
www.cloverdalepaint.com

1.4. Emergency telephone number

Emergency number : 613-996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Carcinogenicity, Category 1 H350
Specific target organ toxicity — Repeated exposure, Category 1 H372
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA) :



GHS08

Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) : H350 - May cause cancer.
H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS-CA) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe mist, vapours, spray.
P264 - Wash Skin thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P280 - Wear eye protection, face protection, protective gloves, protective clothing.
P314 - Get medical advice/attention if you feel unwell.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

FORMWORX WB CONCRETE STAIN WHITE BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
Titanium Dioxide	C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO ₂) / CI 77891 / Titanium(IV) oxide / C.I. Pigment White 7 / Pigment White 6 / Titanium dioxide nanoparticles / TITANIUM DIOXIDE / Titanium oxide	(CAS-No.) 13463-67-7	15 - 40	Carc. 2, H351
Hydrated Aluminum Silicate	CI 77004 / KAOLIN / KaC751:D756	(CAS-No.) 1332-58-7	7 - 13	Carc. 1A, H350 STOT RE 1, H372
ETHYLENE GLYCOL BUTYL ETHER	GLYC ETHER EB/BUTYL CELLOSOLVE 2-Butoxy-1-ethanol / Butoxyethanol / Ethanol, 2-butoxy- / Ethylene glycol monobutyl ether / Ethylene glycol n-butyl ether / Hydroxyethyl butyl ether / Ethylene glycol butyl ether / 2-Butoxyethan-1-ol / Ethylene glycol mono-n-butyl ether / 2-n-Butoxyethanol / Butyl glycol / BUTOXYETHANOL / EGBE / EGMBE / Butoxyethanol, 2- / Butyl Cellosolve / Butyl cellosolve / 2-Butyl cellosolve	(CAS-No.) 111-76-2	1 - 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Dermal), H310 Acute Tox. 3 (Inhalation), H331 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 1, H372

Comments : Actual concentrations are withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.
First-aid measures general : IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

No additional information available

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

FORMWORX WB CONCRETE STAIN WHITE BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe mist, vapours, spray.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ETHYLENE GLYCOL BUTYL ETHER (111-76-2)		
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
USA - OSHA	OSHA PEL (TWA) [1]	240 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA - OSHA	Limit value category (OSHA)	prevent or reduce skin absorption
Canada (Quebec)	VEMP (mg/m ³)	97 mg/m ³
Canada (Quebec)	VEMP (ppm)	20 ppm
Alberta	OEL TWA (mg/m ³)	97 mg/m ³
Alberta	OEL TWA (ppm)	20 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Brunswick	OEL TWA (mg/m ³)	121 mg/m ³
New Brunswick	OEL TWA (ppm)	25 ppm
New Foundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (ppm)	30 ppm
Nunavut	OEL TWA (ppm)	20 ppm
Northwest Territories	OEL STEL (ppm)	30 ppm
Northwest Territories	OEL TWA (ppm)	20 ppm
Ontario	OEL TWA (ppm)	20 ppm
Prince Edward Island	OEL TWA (ppm)	20 ppm
Saskatchewan	OEL STEL (ppm)	30 ppm
Saskatchewan	OEL TWA (ppm)	20 ppm
Yukon	OEL STEL (mg/m ³)	720 mg/m ³
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m ³)	240 mg/m ³
Yukon	OEL TWA (ppm)	50 ppm
Hydrated Aluminum Silicate (1332-58-7)		
USA - ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
USA - OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Canada (Quebec)	VEMP (mg/m ³)	5 mg/m ³ (containing no Asbestos and <1% Crystalline silica-respirable dust)
Alberta	OEL TWA (mg/m ³)	2 mg/m ³ (respirable)
British Columbia	OEL TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate)

FORMWORX WB CONCRETE STAIN WHITE BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Hydrated Aluminum Silicate (1332-58-7)		
Manitoba	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica-particulate matter, respirable particulate matter)
New Brunswick	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable fraction)
New Foundland & Labrador	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica-particulate matter, respirable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica-particulate matter, respirable particulate matter)
Nunavut	OEL STEL (mg/m³)	4 mg/m³ (respirable fraction)
Nunavut	OEL TWA (mg/m³)	2 mg/m³ (respirable fraction)
Northwest Territories	OEL STEL (mg/m³)	4 mg/m³ (respirable fraction)
Northwest Territories	OEL TWA (mg/m³)	2 mg/m³ (respirable fraction)
Ontario	OEL TWA (mg/m³)	2 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable)
Prince Edward Island	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica-particulate matter, respirable particulate matter)
Saskatchewan	OEL STEL (mg/m³)	4 mg/m³ (respirable fraction)
Saskatchewan	OEL TWA (mg/m³)	2 mg/m³ (respirable fraction)
Yukon	OEL STEL (mg/m³)	20 mg/m³
Yukon	OEL TWA (mg/m³)	30 mppcf

Titanium Dioxide (13463-67-7)		
USA - ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
USA - OSHA	OSHA PEL (TWA) [1]	15 mg/m³ (total dust)
Canada (Quebec)	VEMP (mg/m³)	10 mg/m³ (containing no Asbestos and <1% Crystalline silica-total dust)
Alberta	OEL TWA (mg/m³)	10 mg/m³
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (total dust)
Manitoba	OEL TWA (mg/m³)	10 mg/m³
New Brunswick	OEL TWA (mg/m³)	10 mg/m³
New Foundland & Labrador	OEL TWA (mg/m³)	10 mg/m³
Nova Scotia	OEL TWA (mg/m³)	10 mg/m³
Nunavut	OEL STEL (mg/m³)	20 mg/m³
Nunavut	OEL TWA (mg/m³)	10 mg/m³
Northwest Territories	OEL STEL (mg/m³)	20 mg/m³
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³
Ontario	OEL TWA (mg/m³)	10 mg/m³
Prince Edward Island	OEL TWA (mg/m³)	10 mg/m³
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³
Yukon	OEL STEL (mg/m³)	20 mg/m³
Yukon	OEL TWA (mg/m³)	30 mppcf

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
 Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

FORMWORX WB CONCRETE STAIN WHITE BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: white
Odour	: Amine-like
Odour threshold	: No data available
pH	: 8.5 - 9.5
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: $\approx 0^{\circ}\text{C}$
Boiling point	: $\approx 100^{\circ}\text{C}$
Flash point	: $> 93^{\circ}\text{C}$
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50°C	: No data available
Specific gravity	: 1.24
Density	: 10.4 lb/gal
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: $< 50\text{ g/l}$
-------------	---------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

ETHYLENE GLYCOL BUTYL ETHER (111-76-2)

LD50 oral rat	470 mg/kg
LD50 dermal rabbit	99 mg/kg
LC50 inhalation rat (ppm)	486 ppm/4h

Hydrated Aluminum Silicate (1332-58-7)

LD50 oral rat	$> 5000\text{ mg/kg}$
LD50 dermal rat	$> 5000\text{ mg/kg}$

FORMWORX WB CONCRETE STAIN WHITE BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Titanium Dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg
Skin corrosion/irritation	: Not classified pH: 8.5 - 9.5
Serious eye damage/irritation	: Not classified pH: 8.5 - 9.5
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

ETHYLENE GLYCOL BUTYL ETHER (111-76-2)

LC50 fish 1	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 fish 2	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

ETHYLENE GLYCOL BUTYL ETHER (111-76-2)

Log Pow	0.81 (at 25 °C)
---------	-----------------

12.4. Mobility in soil

ETHYLENE GLYCOL BUTYL ETHER (111-76-2)

Log Pow	0.81 (at 25 °C)
---------	-----------------

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

Not regulated for transport

14.2. Transport information/DOT

Department of Transport

Not regulated for transport

14.3. Air and sea transport

IMDG

Not regulated for transport

IATA

Not regulated for transport

SECTION 15: Regulatory information

FORMWORX WB CONCRETE STAIN WHITE BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

15.1. National regulations

ETHYLENE GLYCOL BUTYL ETHER (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

Hydrated Aluminum Silicate (1332-58-7)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

ETHYLENE GLYCOL BUTYL ETHER (111-76-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Hydrated Aluminum Silicate (1332-58-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Titanium Dioxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

Date of issue : 06/16/2017

Revision date : 09/11/2023

Full text of H-statements:

H227	Combustible liquid
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

SDS Canada (GHS) - Cloverdale

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product