

SUNFAST EXTERIOR WATER-BORNE WOOD FINISH SATIN - CEDAR TONE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 05/14/2018

Revision date: 04/15/2021

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Product name : SUNFAST EXTERIOR WATER-BORNE WOOD FINISH SATIN - CEDAR TONE
Product code : 56615
Product group : Trade product

1.2. Recommended use and restrictions on use

Recommended use : Coatings and paints

1.3. Supplier

Cloverdale Paint Inc.
400- 2630 Croydon Drive
V3Z 6T3 SURREY - CANADA
T 1-(604)-596-6261
www.cloverdalepaint.com

1.4. Emergency telephone number

Emergency number : 613-996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Health hazard not otherwise classified, category 1 HHNOC
Corrosive to metals, Category 1 H290
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2A H319
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA) :



Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) : H290 - May be corrosive to metals.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
HHNOC

Precautionary statements (GHS-CA) : P234 - Keep only in original container.
P264 - Wash Skin thoroughly after handling.
P280 - Wear eye protection, face protection, protective gloves, protective clothing.
P302+P352 - IF ON SKIN: Wash with plenty of soap & water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P390 - Absorb spillage to prevent material damage.
P406 - Store in corrosive resistant container with a resistant inner liner.

2.3. Other hazards

No additional information available

SUNFAST EXTERIOR WATER-BORNE WOOD FINISH SATIN - CEDAR TONE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
Triethylamine	(Diethylamino)ethane / Ethanamine, N,N-diethyl- / Triethyl amine / N,N-Diethylethanamine	(CAS-No.) 121-44-8	1.3	HHNOC 1, HHNOC Flam. Liq. 2, H225 Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a physician immediately.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Immediately call a POISON CENTER/doctor.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell. Immediately call a POISON CENTER/doctor.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction. May cause moderate irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation. May cause eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

No additional information available

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SUNFAST EXTERIOR WATER-BORNE WOOD FINISH SATIN - CEDAR TONE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Floors, walls and other surfaces in the hazard area must be cleaned regularly.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store locked up. Store in a well-ventilated place. Keep cool. Store in a closed container.
- Incompatible materials : Metals.
- Storage area : Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Triethylamine (121-44-8)		
USA - ACGIH	ACGIH TWA (ppm)	0.5 ppm
USA - ACGIH	ACGIH STEL (ppm)	1 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m³)	100 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	25 ppm
Canada (Quebec)	VECD (mg/m³)	61.5 mg/m³
Canada (Quebec)	VECD (ppm)	15 ppm
Canada (Quebec)	VEMP (mg/m³)	20.5 mg/m³
Canada (Quebec)	VEMP (ppm)	5 ppm
Alberta	OEL STEL (mg/m³)	12 mg/m³
Alberta	OEL STEL (ppm)	3 ppm
Alberta	OEL TWA (mg/m³)	4.1 mg/m³
Alberta	OEL TWA (ppm)	1 ppm
British Columbia	OEL STEL (ppm)	1 ppm
British Columbia	OEL TWA (ppm)	0.5 ppm
Manitoba	OEL STEL (ppm)	1 ppm
Manitoba	OEL TWA (ppm)	0.5 ppm
New Brunswick	OEL STEL (mg/m³)	12 mg/m³
New Brunswick	OEL STEL (ppm)	3 ppm
New Brunswick	OEL TWA (mg/m³)	4.1 mg/m³
New Brunswick	OEL TWA (ppm)	1 ppm
New Foundland & Labrador	OEL STEL (ppm)	1 ppm
New Foundland & Labrador	OEL TWA (ppm)	0.5 ppm
Nova Scotia	OEL STEL (ppm)	1 ppm
Nova Scotia	OEL TWA (ppm)	0.5 ppm
Nunavut	OEL STEL (ppm)	3 ppm
Nunavut	OEL TWA (ppm)	1 ppm
Northwest Territories	OEL STEL (ppm)	3 ppm
Northwest Territories	OEL TWA (ppm)	1 ppm
Ontario	OEL STEL (ppm)	1 ppm
Ontario	OEL TWA (ppm)	0.5 ppm
Prince Edward Island	OEL STEL (ppm)	1 ppm
Prince Edward Island	OEL TWA (ppm)	0.5 ppm
Saskatchewan	OEL STEL (ppm)	3 ppm

SUNFAST EXTERIOR WATER-BORNE WOOD FINISH SATIN - CEDAR TONE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Triethylamine (121-44-8)		
Saskatchewan	OEL TWA (ppm)	1 ppm
Yukon	OEL STEL (mg/m³)	150 mg/m³
Yukon	OEL STEL (ppm)	40 ppm
Yukon	OEL TWA (mg/m³)	100 mg/m³
Yukon	OEL TWA (ppm)	25 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Protective gloves

Eye protection:

Safety glasses. Chemical goggles or face shield

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Colourless
Odour	: Amine-like
Odour threshold	: No data available
pH	: 7.5 - 8.5
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: 0 °C
Boiling point	: 100 °C
Flash point	: > 100 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Specific gravity	: 1.029
Density	: 8.58 lb/gal
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : < 140 g/l

SUNFAST EXTERIOR WATER-BORNE WOOD FINISH SATIN - CEDAR TONE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: metals.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Triethylamine (121-44-8)	
LD50 oral rat	460 mg/kg
LD50 dermal rabbit	415 mg/kg
LC50 inhalation rat (ppm)	1250 ppm/4h

Skin corrosion/irritation	: Causes skin irritation. pH: 7.5 - 8.5
Serious eye damage/irritation	: Causes serious eye irritation. pH: 7.5 - 8.5
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction. May cause moderate irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation. May cause eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

Triethylamine (121-44-8)	
LC50 fish 1	43.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	200 mg/l (Exposure time: 48 h - Species: Daphnia magna)
BCF fish 1	< 4.9
Log Pow	1.45

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Triethylamine (121-44-8)	
BCF fish 1	< 4.9

SUNFAST EXTERIOR WATER-BORNE WOOD FINISH SATIN - CEDAR TONE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Triethylamine (121-44-8)

Log Pow	1.45
---------	------

12.4. Mobility in soil

Triethylamine (121-44-8)

Log Pow	1.45
---------	------

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

Not regulated for transport

14.2. Transport information/DOT

Department of Transport

Not regulated for transport

14.3. Air and sea transport

IMDG

Not regulated for transport

IATA

Not regulated for transport

SECTION 15: Regulatory information

15.1. National regulations

Triethylamine (121-44-8)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Triethylamine (121-44-8)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16: Other information

Date of issue : 05/14/2018

Revision date : 04/15/2021

Full text of H-statements:

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.

SUNFAST EXTERIOR WATER-BORNE WOOD FINISH SATIN - CEDAR TONE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H402	Harmful to aquatic life

SDS Canada (GHS)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product