

SHARKSKIN DECK & SIDING TRANSLUCENT HONEY MAPLE STAIN

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 04/17/2017

Revision date: 02/27/2018

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Product name : SHARKSKIN DECK & SIDING TRANSLUCENT HONEY MAPLE STAIN
Product code : 72511
Product group : Trade product

1.2. Recommended use and restrictions on use

Recommended use : Coatings and paints

1.3. Supplier

Cloverdale Paint Inc.
400- 2630 Croydon Drive
V3Z 6T3 SURREY - CANADA
T 1-(604)-596-6261
www.cloverdalepaint.com

1.4. Emergency telephone number

Emergency number : 613-996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Flammable liquids, H226
Category 3
Skin sensitisation, H317
Category 1
Germ cell mutagenicity, H340
Category 1
Carcinogenicity, H350
Category 1
Hazardous to the H402
aquatic environment —
Acute Hazard,
Category 3
Hazardous to the H412
aquatic environment —
Chronic Hazard,
Category 3

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA) :



Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) :

H226 - Flammable liquid and vapour.
H317 - May cause an allergic skin reaction.
H340 - May cause genetic defects (Inhalation, oral).
H350 - May cause cancer (Inhalation, oral).
H402 - Harmful to aquatic life
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (GHS-CA) :

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment.

SHARKSKIN DECK & SIDING TRANSLUCENT HONEY MAPLE STAIN

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P242 - Use only non-sparking tools.
P243 - Take action to prevent static discharges.
P261 - Avoid breathing fume, gas, mist, spray, vapours.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective gloves.
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P321 - Specific treatment (see In all cases of doubt, or when symptoms persist, seek medical attention on this label)
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use carbon dioxide (CO₂), foam, Dry chemical, Water fog to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
MINERAL SPIRITS	Naphtha (petroleum), heavy alkylate / Naphtha, (petroleum), heavy alkylate / Heavy alkylate naphtha / Naphtha (petroleum), heavy alkylate - low boiling point modified naphtha / Naphtha, petroleum, heavy alkylate (A complex combination of hydrocarbons produced by distillation of the reaction products of isobutane with monoolefinic hydrocarbons usually ranging in carbon numbers from C3-5. It consists of predominantly branched chain saturated hydrocarbons having carbon numbers predominantly in the range of C9-12 and boiling in the range of approximately 150-220°C.) / Petroleum distillate, heavy alkylated / Lignoine (petroleum), heavy alkylate	(CAS-No.) 64741-65-7	20.9	Flam. Liq. 3, H226 Acute Tox. 3 (Inhalation:vapour), H331 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Titanium Dioxide	C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO ₂) / CI 77891 / Titanium(IV) oxide / C.I. Pigment White 7 / Pigment White 6 / Titanium dioxide nanoparticles / TITANIUM DIOXIDE / Titanium oxide	(CAS-No.) 13463-67-7	0.7	Carc. 2, H351
3-iodo-2-propynyl BUTYL CARBAMATE	Carbamate, 3-iodo-2-propynyl butyl- / 3-iodo-2-propynyl butylcarbamate / 3-iodo-2-propynyl n-butylcarbamate / Carbamic acid, butyl-, 3-iodo-2-propynyl ester / Iodo-2-propynylbutylcarbamate, 3- / Iodocarb / IPBC / 3-iodo-2-propynylbutylcarbamate / Carbamic acid, N-butyl-, 3-iodo-2-propyn-1-yl ester / Iodopropynyl butylcarbamate / IODOPROPYNYL BUTYLCARBAMATE / 3-iodo-2-propynyl-n-butylcarbamate	(CAS-No.) 55406-53-6	0.4	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

SHARKSKIN DECK & SIDING TRANSLUCENT HONEY MAPLE STAIN

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
LIGHT ALIPHATIC SOLVENT NAPHTHA	Solvent naphtha (petroleum), light aliphatic / Naphtha, petroleum, light aliphatic / Solvent naphtha light aliphatic / Naphtha, light aliphatic solvent / Light aliphatic solvent naphtha (petroleum) / Aliphatic light naphtha / Solvent naphtha (petroleum), light aliphatic - low boiling point naphtha / Solvent naphtha(petroleum), light aliphatic / Solvent naphtha, petroleum, light aliphatic (A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C5-10 and boiling in the range of approximately 35-160°C.) / Light aliphatic solvent naphtha	(CAS-No.) 64742-89-8	0.3	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
2-Butanone Oxime	Methyl ethyl ketoxime / Butan-2-one oxime / Butanone oxime / Ethyl methyl ketoxime / 2-Butanone oxime / Ethyl methyl ketone oxime / Methyl ethyl ketone oxime / MEKO / 2-Butanonoxime	(CAS-No.) 96-29-7	0.3	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	Naphtha (petroleum), hydrotreated heavy / Hydrotreated heavy naphtha / Naphtha, (petroleum), hydrotreated heavy / Hydrotreated heavy naphtha (petroleum) / Naphtha (petroleum), hydrotreated heavy - low boiling point thermally cracked naphtha / Isopar 350 / White spirit type 3 / Aliphatic oil / Naphtha, petroleum, hydrotreated heavy (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6-13 and boiling in the range of approximately 65-230°C.) / Synthetic isoparaffin, C6-13 / Naphtha (petroleum), hydrotreated heavy - low boiling point hydrogen treated naphtha / C10-12 ALKANE/CYCLOALKANE / Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha / Naphtha, petroleum, hydrotreated, heavy / Lignoine (petroleum), hydrotreated heavy	(CAS-No.) 64742-48-9	0.3	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause moderate irritation. Repeated or prolonged contact may cause sensitization of the skin (dermatitis, reddening,...). May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause severe irritation.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SHARKSKIN DECK & SIDING TRANSLUCENT HONEY MAPLE STAIN

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Dry chemical. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Flammable liquid and vapour.

Explosion hazard : May form flammable/explosive vapour-air mixture.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Eliminate all ignition sources if safe to do so. Evacuate area. Exercise caution when fighting any chemical fire. Use extinguishing agent suitable for surrounding fire. Use water spray or fog for cooling exposed containers. Wear personal protective equipment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Eliminate every possible source of ignition. Evacuate area. Ground and bond container and receiving equipment. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Ventilate area. Wear personal protective equipment.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect spillage. Dispose of contaminated materials in accordance with current regulations.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Additional hazards when processed : Avoid breathing dust, mist or spray. Avoid contact with skin and eyes. Ensure good ventilation of the work station. Ground and bond container and receiving equipment. Handle carefully.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment. Keep container closed when not in use. Provide local exhaust or general room ventilation. Use only non-sparking tools.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium Dioxide (13463-67-7)		
USA - ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
USA - OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)
Canada (Quebec)	VEMP (mg/m³)	10 mg/m³ (containing no Asbestos and <1% Crystalline silica-total dust)
Alberta	OEL TWA (mg/m³)	10 mg/m³

SHARKSKIN DECK & SIDING TRANSLUCENT HONEY MAPLE STAIN

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Titanium Dioxide (13463-67-7)		
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (total dust)
Manitoba	OEL TWA (mg/m ³)	10 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
New Foundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³
Ontario	OEL TWA (mg/m ³)	10 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	30 mppcf

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gas mask. Gloves. Protective clothing. Safety glasses.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: amber
Odour	: aromatic
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: ≈ 53 °C CLOSED CUP

SHARKSKIN DECK & SIDING TRANSLUCENT HONEY MAPLE STAIN

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Specific gravity	: 0.92
Density	: 7.7 lb/gal
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: < 250 g/l
-------------	-------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: Flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

3-iodo-2-propynyl butyl carbamate (55406-53-6)

LD50 oral rat	1470 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

2-Butanone Oxime (96-29-7)

LD50 oral rat	930 mg/kg
LD50 dermal rabbit	1000 - 1800 mg/kg
LC50 inhalation rat (mg/l)	> 4800 mg/m ³ (Exposure time: 4 h)

MINERAL SPIRITS (64741-65-7)

LD50 oral rat	> 7000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.04 mg/l/4h

LIGHT ALIPHATIC SOLVENT NAPHTHA (64742-89-8)

LD50 dermal rabbit	3000 mg/kg
--------------------	------------

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

LD50 oral rat	> 6000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (mg/l)	> 8500 mg/m ³ (Exposure time: 4 h)

Titanium Dioxide (13463-67-7)

LD50 oral rat	> 10000 mg/kg
---------------	---------------

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects (Inhalation, oral).
Carcinogenicity	: May cause cancer (Inhalation, oral).
Reproductive toxicity	: Not classified

SHARKSKIN DECK & SIDING TRANSLUCENT HONEY MAPLE STAIN

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Likely routes of exposure	: Dermal. Inhalation. oral.
Symptoms/effects after inhalation	: May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause moderate irritation. Repeated or prolonged contact may cause sensitization of the skin (dermatitis, reddening,...). May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause severe irritation.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life. Harmful to aquatic life with long lasting effects.
Acute aquatic toxicity	: Harmful to aquatic life.
Chronic aquatic toxicity	: Harmful to aquatic life with long lasting effects.

3-iodo-2-propynyl butyl carbamate (55406-53-6)

LC50 fish 1	0.14 - 0.32 mg/l (Exposure time: 96 h - Species: <i>Lepomis macrochirus</i> [flow-through])
LC50 fish 2	0.049 - 0.079 mg/l (Exposure time: 96 h - Species: <i>Oncorhynchus mykiss</i> [flow-through])

2-Butanone Oxime (96-29-7)

LC50 fish 1	777 - 914 mg/l (Exposure time: 96 h - Species: <i>Pimephales promelas</i> [flow-through])
LC50 fish 2	760 mg/l (Exposure time: 96 h - Species: <i>Poecilia reticulata</i> [static])
EC50 Daphnia 1	750 mg/l (Exposure time: 48 h - Species: <i>Daphnia magna</i>)
EC50 72h algae (1)	83 mg/l (Species: <i>Desmodesmus subspicatus</i>)
BCF fish 1	0.5 - 5.8
Log Pow	0.65 (at 25 °C)

MINERAL SPIRITS (64741-65-7)

EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: <i>Mysidopsis bahia</i>)
EC50 72h algae (1)	30000 mg/l (Species: <i>Pseudokirchneriella subcapitata</i>)

LIGHT ALIPHATIC SOLVENT NAPHTHA (64742-89-8)

EC50 72h algae (1)	4700 mg/l (Species: <i>Pseudokirchneriella subcapitata</i>)
--------------------	--

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

LC50 fish 1	2200 mg/l (Exposure time: 96 h - Species: <i>Pimephales promelas</i>)
-------------	--

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

2-Butanone Oxime (96-29-7)

BCF fish 1	0.5 - 5.8
Log Pow	0.65 (at 25 °C)

12.4. Mobility in soil

2-Butanone Oxime (96-29-7)

Log Pow	0.65 (at 25 °C)
---------	-----------------

12.5. Other adverse effects

Ozone	: Not classified
-------	------------------

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container.

SHARKSKIN DECK & SIDING TRANSLUCENT HONEY MAPLE STAIN

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

UN-No. (TDG)	: UN1263
Packing group	: III - Minor Danger
TDG Primary Hazard Classes	: 3 - Class 3 - Flammable Liquids
Transport document description	: UN1263 PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass), 3, III
Proper Shipping Name (Transportation of Dangerous Goods)	: PAINT including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass
Hazard labels (TDG)	: 3 - Flammable liquids



TDG Special Provisions	: 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (by dry mass). 142 - The following shipping names may be used to meet the requirements of Part 3 (Documentation) and Part 4 (Dangerous Goods Safety Marks) when these dangerous goods are offered for transport in the same means of containment: (a)"PAINT RELATED MATERIAL" may be used for a means of containment containing both paint and paint related material; (b)"PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" may be used for a means of containment containing both paint, corrosive, flammable, and paint related material, corrosive, flammable; (c)"PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" may be used for a means of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d)"PRINTING INK RELATED MATERIAL" may be used for a means of containment containing both printing ink and printing ink related material. SOR/2014-306
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 60 L

14.2. Transport information/DOT

Department of Transport

DOT NA no.	: UN1263
UN-No.(DOT)	: 1263
Packing group (DOT)	: III - Minor Danger
Transport document description	: UN1263 Paint, 3, III
Proper Shipping Name (DOT)	: Paint
Contains Statement Field Selection (DOT)	:
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Division (DOT)	: 3
Hazard labels (DOT)	: 3 - Flammable liquid



Dangerous for the environment	: No
-------------------------------	------

SHARKSKIN DECK & SIDING TRANSLUCENT HONEY MAPLE STAIN

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

DOT Special Provisions (49 CFR 172.102)	: 367 - For the purposes of documentation and package marking: a. The proper shipping name "Paint related material" may be used for consignments of packages containing "Paint" and "Paint related material" in the same package; b. The proper shipping name "Paint related material, corrosive, flammable" may be used for consignments of packages containing "Paint, corrosive, flammable" and "Paint related material, corrosive, flammable" in the same package; c. The proper shipping name "Paint related material, flammable, corrosive" may be used for consignments of packages containing "Paint, flammable, corrosive" and "Paint related material, flammable, corrosive" in the same package; and d. The proper shipping name "Printing ink related material" may be used for consignments of packages containing "Printing ink" and "Printing ink related material" in the same package. B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 173
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

14.3. Air and sea transport

IMDG

UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Transport document description (IMDG)	: UN 1263 PAINT, 3, III
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger

IATA

UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: Paint
Transport document description (IATA)	: UN 1263 Paint, 3, III
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. National regulations

3-IODO-2-PROPYNYL BUTYL CARBAMATE (55406-53-6)

Listed on the Canadian DSL (Domestic Substances List)

2-Butanone Oxime (96-29-7)

Listed on the Canadian DSL (Domestic Substances List)

MINERAL SPIRITS (64741-65-7)

Listed on the Canadian DSL (Domestic Substances List)

SHARKSKIN DECK & SIDING TRANSLUCENT HONEY MAPLE STAIN

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

LIGHT ALIPHATIC SOLVENT NAPHTHA (64742-89-8)

Listed on the Canadian DSL (Domestic Substances List)

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

3-IODO-2-PROPYNYL BUTYL CARBAMATE (55406-53-6)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

2-Butanone Oxime (96-29-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

Toxic Substance (CEPA – Schedule I)

Yes

MINERAL SPIRITS (64741-65-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

LIGHT ALIPHATIC SOLVENT NAPHTHA (64742-89-8)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

Titanium Dioxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

Date of issue : 04/17/2017

Revision date : 02/27/2018

SHARKSKIN DECK & SIDING TRANSLUCENT HONEY MAPLE STAIN

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Full text of H-statements:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H227	Combustible liquid
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS Canada (GHS)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product