

SECTION 1: Identification

1.1. Product identifier

Product form	: Mixture
Product name	: SELF-PRIMING SPEED ENAMEL L.F. YELLOW BASE
Product code	: 76345
Product group	: Trade product

1.2. Recommended use and restrictions on use

Recommended use	: Coatings and paints
-----------------	-----------------------

1.3. Supplier

Cloverdale Paint Inc.
400- 2630 Croydon Drive
V3Z 6T3 SURREY - CANADA
T 1-(604)-596-6261
www.cloverdalepaint.com

1.4. Emergency telephone number

Emergency number	: 613-996-6666
------------------	----------------

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Skin sensitisation, Category 1	H317
Germ cell mutagenicity, Category 1	H340
Carcinogenicity, Category 1	H350
Reproductive toxicity, Category 2	H361
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity — Repeated exposure, Category 1	H372
Hazardous to the aquatic environment — Acute Hazard, Category 1	H400
Full text of H statements : see section 16	

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA)



Signal word (GHS-CA)

: Danger

Hazard statements (GHS-CA)

: H225 - Highly flammable liquid and vapour.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H336 - May cause drowsiness or dizziness.
H340 - May cause genetic defects.
H350 - May cause cancer.
H361 - Suspected of damaging fertility or the unborn child.
H372 - Causes damage to organs through prolonged or repeated exposure.
H400 - Very toxic to aquatic life.

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, ventilating, lighting equipment.
P260 - Do not breathe mist, vapours, spray.
P264 - Wash Skin thoroughly after handling.

Precautionary statements (GHS-CA)

SELF-PRIMING SPEED ENAMEL L.F. YELLOW BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear eye protection, face protection, protective gloves, protective clothing.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with soap and water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P314 - Get medical advice/attention if you feel unwell.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use carbon dioxide (CO₂), foam, dry chemical to extinguish.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
PURE XYLENE	Benzene, dimethyl- / Dimethylbenzene (mixed isomers) / Xylene / Xylene (all isomers) / Xylene (mixed isomers) / Xylene (o-, m-, p- isomers) / Xylenes / Xylenes (mixed isomers) / Dimethylbenzene / Xylol / Benzene, dimethyl-, mixed isomers / Xylenes (all isomers) / XYLENE / Dimethylbenzenes / Xylene isomers mixture / Dimethylbenzene (2-, 3-, 4-isomers) / Dimethylbenzene (mixed 2-, 3-, 4-isomers) / Xylenes (ortho-, meta-, para- isomers) / C8 Disubstituted benzenes / Xylenes - all isomers / Xylene - all isomers / Xylene, all isomers / Xylene, mixed isomers	(CAS-No.) 1330-20-7	33.8	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400
Toluene	Benzene, methyl- / Methylbenzene / Phenylmethane / TOLUENE	(CAS-No.) 108-88-3	15.1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
ETHYLBENZENE	Benzene, ethyl- / Phenylethane	(CAS-No.) 100-41-4	8.2	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
ETHYLENE GLYCOL BUTYL ETHER	GLYC ETHER EB/BUTYL CELLOSOLVE 2-Butoxy-1-ethanol / Butoxyethanol / Ethanol, 2-butoxy- / Ethylene glycol monobutyl ether / Ethylene glycol n-butyl ether / Hydroxyethyl butyl ether / Ethylene glycol butyl ether / 2-Butoxyethan-1-ol / Ethylene glycol mono-n-butyl ether / 2-n-Butoxyethanol / Butyl glycol / BUTOXYETHANOL / EGBE / EGMBE / Butoxyethanol, 2- / Butyl Cellosolve / Butyl cellosolve / 2-Butyl cellosolve	(CAS-No.) 111-76-2	1	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Dermal), H310 Acute Tox. 3 (Inhalation), H331 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 1, H372

SELF-PRIMING SPEED ENAMEL L.F. YELLOW BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
2-Butanone Oxime	Methyl ethyl ketoxime / Butan-2-one oxime / Butanone oxime / Ethyl methyl ketoxime / 2-Butanone oxime / Ethyl methyl ketone oxime / Methyl ethyl ketone oxime / MEKO / 2-Butanonoxime	(CAS-No.) 96-29-7	0.3	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation:vapour), H331 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351
LIGHT ALIPHATIC SOLVENT NAPHTHA	Solvent naphtha (petroleum), light aliphatic / Naphtha, petroleum, light aliphatic / Solvent naphtha light aliphatic / Naphtha, light aliphatic solvent / Light aliphatic solvent naphtha (petroleum) / Solvent naphtha (petroleum), light aliphatic - low boiling point naphtha / Aliphatic light naphtha / Solvent naphtha(petroleum), light aliphatic / Solvent naphtha, petroleum, light aliphatic (A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C5-10 and boiling in the range of approximately 35-160°C.) / Light aliphatic solvent naphtha	(CAS-No.) 64742-89-8	0.2	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	Naphtha (petroleum), hydrotreated heavy / Hydrotreated heavy naphtha / Naphtha, (petroleum), hydrotreated heavy / Hydrotreated heavy naphtha (petroleum) / Naphtha (petroleum), hydrotreated heavy - low boiling point thermally cracked naphtha / Isopar 350 / White spirit type 3 / Aliphatic oil / C10-12 ALKANE/CYCLOALKANE / Synthetic isoparaffin, C6-13 / Naphtha (petroleum), hydrotreated heavy - low boiling point hydrogen treated naphtha / Naphtha, petroleum, hydrotreated heavy (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6-13 and boiling in the range of approximately 65-230°C.) / Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha / Naphtha, petroleum, hydrotreated, heavy / Lignoine (petroleum), hydrotreated heavy	(CAS-No.) 64742-48-9	0.1	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.
- First-aid measures general : IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

4.3. Immediate medical attention and special treatment, if necessary

- Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

- Suitable extinguishing media : Water fog. Dry powder. Foam. Carbon dioxide.

SELF-PRIMING SPEED ENAMEL L.F. YELLOW BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Highly flammable liquid and vapour.

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe mist, vapours, spray. Avoid contact with skin and eyes.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Toluene (108-88-3)		
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
USA - OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA - OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
USA - OSHA	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	500 ppm Peak (10 minutes)
Canada (Quebec)	VEMP (mg/m ³)	188 mg/m ³
Canada (Quebec)	VEMP (ppm)	50 ppm
Alberta	OEL TWA (mg/m ³)	188 mg/m ³
Alberta	OEL TWA (ppm)	50 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Brunswick	OEL TWA (mg/m ³)	188 mg/m ³
New Brunswick	OEL TWA (ppm)	50 ppm
New Foundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (ppm)	60 ppm

SELF-PRIMING SPEED ENAMEL L.F. YELLOW BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Toluene (108-88-3)		
Nunavut	OEL TWA (ppm)	50 ppm
Northwest Territories	OEL STEL (ppm)	60 ppm
Northwest Territories	OEL TWA (ppm)	50 ppm
Ontario	OEL TWA (ppm)	20 ppm
Prince Edward Island	OEL TWA (ppm)	20 ppm
Saskatchewan	OEL STEL (ppm)	60 ppm
Saskatchewan	OEL TWA (ppm)	50 ppm
Yukon	OEL STEL (mg/m³)	560 mg/m³
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m³)	375 mg/m³
Yukon	OEL TWA (ppm)	100 ppm
ETHYLENE GLYCOL BUTYL ETHER (111-76-2)		
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA - OSHA	Limit value category (OSHA)	prevent or reduce skin absorption
Canada (Quebec)	VEMP (mg/m³)	97 mg/m³
Canada (Quebec)	VEMP (ppm)	20 ppm
Alberta	OEL TWA (mg/m³)	97 mg/m³
Alberta	OEL TWA (ppm)	20 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Brunswick	OEL TWA (mg/m³)	121 mg/m³
New Brunswick	OEL TWA (ppm)	25 ppm
New Foundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (ppm)	30 ppm
Nunavut	OEL TWA (ppm)	20 ppm
Northwest Territories	OEL STEL (ppm)	30 ppm
Northwest Territories	OEL TWA (ppm)	20 ppm
Ontario	OEL TWA (ppm)	20 ppm
Prince Edward Island	OEL TWA (ppm)	20 ppm
Saskatchewan	OEL STEL (ppm)	30 ppm
Saskatchewan	OEL TWA (ppm)	20 ppm
Yukon	OEL STEL (mg/m³)	720 mg/m³
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m³)	240 mg/m³
Yukon	OEL TWA (ppm)	50 ppm
PURE XYLENE (1330-20-7)		
USA - ACGIH	ACGIH TWA (ppm)	100 ppm
USA - ACGIH	ACGIH STEL (ppm)	150 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Canada (Quebec)	VECD (mg/m³)	651 mg/m³
Canada (Quebec)	VECD (ppm)	150 ppm
Canada (Quebec)	VEMP (mg/m³)	434 mg/m³
Canada (Quebec)	VEMP (ppm)	100 ppm
Alberta	OEL STEL (mg/m³)	651 mg/m³
Alberta	OEL STEL (ppm)	150 ppm
Alberta	OEL TWA (mg/m³)	434 mg/m³
Alberta	OEL TWA (ppm)	100 ppm

SELF-PRIMING SPEED ENAMEL L.F. YELLOW BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

PURE XYLENE (1330-20-7)		
British Columbia	OEL STEL (ppm)	150 ppm
British Columbia	OEL TWA (ppm)	100 ppm
Manitoba	OEL STEL (ppm)	150 ppm
Manitoba	OEL TWA (ppm)	100 ppm
New Brunswick	OEL STEL (mg/m³)	651 mg/m³
New Brunswick	OEL STEL (ppm)	150 ppm
New Brunswick	OEL TWA (mg/m³)	434 mg/m³
New Brunswick	OEL TWA (ppm)	100 ppm
New Foundland & Labrador	OEL STEL (ppm)	150 ppm
New Foundland & Labrador	OEL TWA (ppm)	100 ppm
Nova Scotia	OEL STEL (ppm)	150 ppm
Nova Scotia	OEL TWA (ppm)	100 ppm
Nunavut	OEL STEL (ppm)	150 ppm
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (ppm)	150 ppm
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL STEL (ppm)	150 ppm
Ontario	OEL TWA (ppm)	100 ppm
Prince Edward Island	OEL STEL (ppm)	150 ppm
Prince Edward Island	OEL TWA (ppm)	100 ppm
Saskatchewan	OEL STEL (ppm)	150 ppm
Saskatchewan	OEL TWA (ppm)	100 ppm
Yukon	OEL STEL (mg/m³)	650 mg/m³
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m³)	435 mg/m³
Yukon	OEL TWA (ppm)	100 ppm
ETHYLBENZENE (100-41-4)		
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Canada (Quebec)	VECD (mg/m³)	543 mg/m³
Canada (Quebec)	VECD (ppm)	125 ppm
Canada (Quebec)	VEMP (mg/m³)	434 mg/m³
Canada (Quebec)	VEMP (ppm)	100 ppm
Alberta	OEL STEL (mg/m³)	543 mg/m³
Alberta	OEL STEL (ppm)	125 ppm
Alberta	OEL TWA (mg/m³)	434 mg/m³
Alberta	OEL TWA (ppm)	100 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Brunswick	OEL STEL (mg/m³)	543 mg/m³
New Brunswick	OEL STEL (ppm)	125 ppm
New Brunswick	OEL TWA (mg/m³)	434 mg/m³
New Brunswick	OEL TWA (ppm)	100 ppm
New Foundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (ppm)	125 ppm
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (ppm)	125 ppm

SELF-PRIMING SPEED ENAMEL L.F. YELLOW BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

ETHYLBENZENE (100-41-4)		
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL TWA (ppm)	20 ppm
Prince Edward Island	OEL TWA (ppm)	20 ppm
Saskatchewan	OEL STEL (ppm)	125 ppm
Saskatchewan	OEL TWA (ppm)	100 ppm
Yukon	OEL STEL (mg/m³)	545 mg/m³
Yukon	OEL STEL (ppm)	125 ppm
Yukon	OEL TWA (mg/m³)	435 mg/m³
Yukon	OEL TWA (ppm)	100 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Yellow
Odour	: mild
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 110 - 138 °C
Flash point	: ≈ 6 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Specific gravity	: 0.99
Density	: 8.2 lb/gal
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : < 585 g/l

SELF-PRIMING SPEED ENAMEL L.F. YELLOW BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: Highly flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h

2-Butanone Oxime (96-29-7)	
LD50 oral rat	930 mg/kg
LD50 dermal rabbit	1000 - 1800 mg/kg
LC50 inhalation rat (mg/l)	> 4.83 mg/l/4h

ETHYLENE GLYCOL BUTYL ETHER (111-76-2)	
LD50 oral rat	470 mg/kg
LD50 dermal rabbit	99 mg/kg
LC50 inhalation rat (ppm)	486 ppm/4h

PURE XYLENE (1330-20-7)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 4350 mg/kg
LC50 inhalation rat (mg/l)	29.08 mg/l/4h

ETHYLBENZENE (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat (mg/l)	17.4 mg/l/4h

LIGHT ALIPHATIC SOLVENT NAPHTHA (64742-89-8)	
LD50 dermal rabbit	3000 mg/kg

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
LD50 oral rat	> 6000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (mg/l)	> 8500 mg/m ³ (Exposure time: 4 h)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Very toxic to aquatic life.
-------------------	-------------------------------

SELF-PRIMING SPEED ENAMEL L.F. YELLOW BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Toluene (108-88-3)	
LC50 fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
2-Butanone Oxime (96-29-7)	
LC50 fish 1	777 - 914 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	760 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
EC50 Daphnia 1	750 mg/l (Exposure time: 48 h - Species: Daphnia magna)
ETHYLENE GLYCOL BUTYL ETHER (111-76-2)	
LC50 fish 1	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 fish 2	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
PURE XYLENE (1330-20-7)	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
ETHYLBENZENE (100-41-4)	
LC50 fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
LC50 fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
LC50 fish 1	2200 mg/l (Exposure time: 96 h - Species: Pimephales promelas)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Toluene (108-88-3)	
Log Pow	2.7
2-Butanone Oxime (96-29-7)	
BCF fish 1	0.5 - 5.8
Log Pow	0.65 (at 25 °C)
ETHYLENE GLYCOL BUTYL ETHER (111-76-2)	
Log Pow	0.81 (at 25 °C)
PURE XYLENE (1330-20-7)	
BCF fish 1	0.6 - 15
Log Pow	2.77 - 3.15
ETHYLBENZENE (100-41-4)	
BCF fish 1	15
Log Pow	3.2

12.4. Mobility in soil

Toluene (108-88-3)	
Log Pow	2.7
2-Butanone Oxime (96-29-7)	
Log Pow	0.65 (at 25 °C)
ETHYLENE GLYCOL BUTYL ETHER (111-76-2)	
Log Pow	0.81 (at 25 °C)
PURE XYLENE (1330-20-7)	
Log Pow	2.77 - 3.15
ETHYLBENZENE (100-41-4)	
Log Pow	3.2

12.5. Other adverse effects

No additional information available

SELF-PRIMING SPEED ENAMEL L.F. YELLOW BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 13: Disposal considerations

13.1. Disposal methods

- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

- UN-No. (TDG) : UN1263
- Packing group : II - Medium Danger
- TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids
- Transport document description : UN1263 PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass), 3, II
- Proper Shipping Name (Transportation of Dangerous Goods) : PAINT
including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass

- Hazard labels (TDG) : 3 - Flammable liquids



- TDG Special Provisions : 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (by dry mass).
142 - The following shipping names may be used to meet the requirements of Part 3 (Documentation) and Part 4 (Dangerous Goods Safety Marks) when these dangerous goods are offered for transport in the same means of containment: (a)"PAINT RELATED MATERIAL" may be used for a means of containment containing both paint and paint related material; (b)"PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" may be used for a means of containment containing both paint, corrosive, flammable, and paint related material, corrosive, flammable; (c)"PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" may be used for a means of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d)"PRINTING INK RELATED MATERIAL" may be used for a means of containment containing both printing ink and printing ink related material. SOR/2014-306

- Explosive Limit and Limited Quantity Index : 5 L
- Excepted quantities (TDG) : E2
- Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 5 L
- Marine pollutant : Yes (IMDG only)



14.2. Transport information/DOT

Department of Transport

- DOT NA no. : UN1263
- UN-No.(DOT) : 1263
- Packing group (DOT) : II - Medium Danger
- Transport document description : UN1263 Paint, 3, II
- Proper Shipping Name (DOT) : Paint
- Contains Statement Field Selection (DOT) :

SELF-PRIMING SPEED ENAMEL L.F. YELLOW BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Division (DOT) : 3
Hazard labels (DOT) : 3 - Flammable liquid



Dangerous for the environment : Yes
Marine pollutant : Yes



DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packagings may be increased to 5 L (1.3 gallons).
367 - For the purposes of documentation and package marking: a. The proper shipping name "Paint related material" may be used for consignments of packages containing "Paint" and "Paint related material" in the same package; b. The proper shipping name "Paint related material, corrosive, flammable" may be used for consignments of packages containing "Paint, corrosive, flammable" and "Paint related material, corrosive, flammable" in the same package; c. The proper shipping name "Paint related material, flammable, corrosive" may be used for consignments of packages containing "Paint, flammable, corrosive" and "Paint related material, flammable, corrosive" in the same package; and d. The proper shipping name "Printing ink related material" may be used for consignments of packages containing "Printing ink" and "Printing ink related material" in the same package.
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail : 5 L
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : 60 L
CFR 175.75)
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
Emergency Response Guide (ERG) Number : 128
Other information : No supplementary information available.

14.3. Air and sea transport

IMDG

UN-No. (IMDG) : 1263
Proper Shipping Name (IMDG) : PAINT

SELF-PRIMING SPEED ENAMEL L.F. YELLOW BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Transport document description (IMDG)	: UN 1263 PAINT, 3, II
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger

IATA

UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: Paint
Transport document description (IATA)	: UN 1263 Paint, 3, II
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger

SECTION 15: Regulatory information

15.1. National regulations

Toluene (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

2-Butanone Oxime (96-29-7)

Listed on the Canadian DSL (Domestic Substances List)

ETHYLENE GLYCOL BUTYL ETHER (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

PURE XYLENE (1330-20-7)

Listed on the Canadian DSL (Domestic Substances List)

ETHYLBENZENE (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

LIGHT ALIPHATIC SOLVENT NAPHTHA (64742-89-8)

Listed on the Canadian DSL (Domestic Substances List)

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Toluene (108-88-3)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Japanese Poisonous and Deleterious Substances Control Law
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

2-Butanone Oxime (96-29-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

ETHYLENE GLYCOL BUTYL ETHER (111-76-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

SELF-PRIMING SPEED ENAMEL L.F. YELLOW BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

PURE XYLENE (1330-20-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Japanese Poisonous and Deleterious Substances Control Law
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

ETHYLBENZENE (100-41-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

LIGHT ALIPHATIC SOLVENT NAPHTHA (64742-89-8)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16: Other information

Date of issue : 05/04/2017

Revision date : 11/06/2019

Full text of H-statements:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H227	Combustible liquid
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

SELF-PRIMING SPEED ENAMEL L.F. YELLOW BASE

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life

SDS Canada (GHS) - Cloverdale

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product