

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
 Product name : CLOVAMASTIC: LOW TEMPERATURE CURE EPOXY, BLACK
 Product code : 83114A
 Product group : Trade product

1.2. Recommended use and restrictions on use

Recommended use : Coatings and paints

1.3. Supplier

Cloverdale Paint Inc.
 400- 2630 Croydon Drive
 V3Z 6T3 Surrey - CANADA
 T 1-(604)-596-6261
btinsley@cloverdalepaint.com - www.cloverdalepaint.com

1.4. Emergency telephone number

Emergency number : CANUTEC 24 hr. Emergency Number (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Flammable liquids Category 2 H225
 Skin sensitization, Category 1 H317
 Carcinogenicity Category 2 H351
 Reproductive toxicity Category 2 H361
 Specific target organ toxicity (repeated exposure) Category 1 H372
 Hazardous to the aquatic environment - Acute Hazard Category 2 H401
 Hazardous to the aquatic environment - Chronic Hazard Category 2 H411
 Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-CA labeling

Hazard pictograms (GHS-CA) :



Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) :

- H225 - Highly flammable liquid and vapour
- H317 - May cause an allergic skin reaction
- H351 - Suspected of causing cancer
- H361 - Suspected of damaging fertility or the unborn child
- H372 - Causes damage to organs through prolonged or repeated exposure
- H401 - Toxic to aquatic life
- H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-CA) :

- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 - Keep container tightly closed.
- P240 - Ground/bond container and receiving equipment.
- P241 - Use explosion-proof electrical, ventilating, lighting equipment
- P260 - Do not breathe mist, vapors, spray.
- P264 - Wash Skin thoroughly after handling.
- P270 - Do not eat, drink or smoke when using this product.
- P272 - Contaminated work clothing should not be allowed out of the workplace.
- P273 - Avoid release to the environment.
- P280 - Wear eye protection, face protection, protective gloves, protective clothing.

CLOVAMASTIC: LOW TEMPERATURE CURE EPOXY, BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with soap and water .
P314 - Get medical advice/attention if you feel unwell.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use carbon dioxide (CO₂), foam, dry chemical to extinguish.
P391 - Collect spillage.
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
M.E.K.	Butan-2-one / 2-Butanone / Ethyl methyl ketone / Methyl acetone / MEK / Butanone	(CAS-No.) 78-93-3	6	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Repr. 2, H361 STOT SE 3, H335
Alkyl (C12-14) glycidyl ether	Alkyl glycidyl ether / Oxirane, mono[(C12-14)-alkyloxy)methyl] derivatives / Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives / Oxirane, mono-(C12-14-alkyloxy)methyl derivatives / Oxirane, 2-[(C12-14-alkyloxy)methyl] derivatives / (C12-14 Alkyl) glycidyl ether / Alkyl(C12-14) glycidyl ether / Oxirane, 2-[(C12-14-alkyloxy)methyl] derivatives / Mono[(C12-14-alkyloxy)methyl]-oxirane derivatives / C12-14 alkyl glycidyl ether	(CAS-No.) 68609-97-2	1.8	Skin Irrit. 2, H315 Skin Sens. 1, H317
CARBON BLACK PIGMENT	C.I. 77266 / C.I. Pigment Black 6 / C.I. Pigment Black 7 / Carbon blacks / Lampblack / CI 77266 / Vegetable carbon / Microjet Black CW / Pigment Black 7 / Coal soot / Coal soots / Channel black / Bonjet Black CW / Carbon Black	(CAS-No.) 1333-86-4	1.5	Carc. 2, H351 Comb. Dust
FURFURYL ALCOHOL	Furan, 2-hydroxymethyl- / Furyl alcohol / 2-Furancarbinol / 2-Furanmethanol / Furfural alcohol / 2-Furylcarbinol / 2-Furylmethanol / 2-Hydroxymethylfuran / Methanol, (2-furyl)- / NCI-C56224 / Furan carbinol / Furfural / Furan-2-ylmethanol / 2-Furfuryl alcohol / Furan-2-ylmethanol / Furyl-2-methanol / Fur-2-ylmethanol	(CAS-No.) 98-00-0	1.2	Flam. Liq. 4, H227 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation), H330 Acute Tox. 3 (Inhalation:vapour), H331 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335 STOT RE 1, H372 Aquatic Acute 3, H402

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.
First-aid measures general : IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/effects after skin contact : May cause moderate irritation. Repeated or prolonged contact may cause sensitization of the skin (dermatitis, reddening,...). May cause an allergic skin reaction.
Symptoms/effects after eye contact : May cause severe irritation.

CLOVAMASTIC: LOW TEMPERATURE CURE EPOXY, BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Dry chemical. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Highly flammable liquid and vapour.

Explosion hazard : May form flammable/explosive vapor-air mixture.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Eliminate all ignition sources if safe to do so. Evacuate area. Exercise caution when fighting any chemical fire. Use extinguishing agent suitable for surrounding fire. Use water spray or fog for cooling exposed containers. Wear personal protective equipment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes. Avoid inhalation of vapor and spray mist. Eliminate every possible source of ignition. Evacuate area. Ground and bond container and receiving equipment. Soak up with absorbent material (for example sand, sawdust, neutral absorbent granule, silica gel). Ventilate area. Wear personal protective equipment.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Dispose of contaminated materials in accordance with current regulations. Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8 "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe mist, vapors, spray. Avoid contact with skin and eyes.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Additional hazards when processed : Avoid breathing dust, mist or spray. Avoid contact with skin and eyes. Ensure good ventilation of the work station. Ground and bond container and receiving equipment. Handle carefully.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep container closed when not in use. Provide local exhaust or general room ventilation. Ground/bond container and receiving equipment. Use only non-sparking tools.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Incompatible products : Oxidizing agent. acids. Bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

CLOVAMASTIC: LOW TEMPERATURE CURE EPOXY, BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

CARBON BLACK PIGMENT (1333-86-4)		
USA - ACGIH	ACGIH TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
USA - OSHA	OSHA PEL (TWA) (mg/m³)	3.5 mg/m³
Canada (Quebec)	VEMP (mg/m³)	3.5 mg/m³
Alberta	OEL TWA (mg/m³)	3.5 mg/m³
British Columbia	OEL TWA (mg/m³)	3 mg/m³ (inhalable)
Manitoba	OEL TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m³)	3.5 mg/m³
New Foundland & Labrador	OEL TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
Nunavut	OEL STEL (mg/m³)	7 mg/m³
Nunavut	OEL TWA (mg/m³)	3.5 mg/m³
Northwest Territories	OEL STEL (mg/m³)	7 mg/m³
Northwest Territories	OEL TWA (mg/m³)	3.5 mg/m³
Ontario	OEL TWA (mg/m³)	3 mg/m³ (inhalable)
Prince Edward Island	OEL TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
Saskatchewan	OEL STEL (mg/m³)	7 mg/m³
Saskatchewan	OEL TWA (mg/m³)	3.5 mg/m³
Yukon	OEL STEL (mg/m³)	7 mg/m³
Yukon	OEL TWA (mg/m³)	3.5 mg/m³
FURFURYL ALCOHOL (98-00-0)		
USA - ACGIH	ACGIH TWA (ppm)	2 ppm
USA - ACGIH	Remark (ACGIH)	URT & eye irr; Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histologic type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiologic studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure)
USA - OSHA	OSHA PEL (TWA) (mg/m³)	200 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	50 ppm
Canada (Quebec)	VECD (mg/m³)	60 mg/m³
Canada (Quebec)	VECD (ppm)	15 ppm
Canada (Quebec)	VEMP (mg/m³)	40 mg/m³
Canada (Quebec)	VEMP (ppm)	10 ppm
Alberta	OEL STEL (mg/m³)	60 mg/m³
Alberta	OEL STEL (ppm)	15 ppm
Alberta	OEL TWA (mg/m³)	40 mg/m³
Alberta	OEL TWA (ppm)	10 ppm
British Columbia	OEL STEL (ppm)	10 ppm
British Columbia	OEL TWA (ppm)	5 ppm
Manitoba	OEL TWA (ppm)	0.2 ppm
New Brunswick	OEL STEL (mg/m³)	60 mg/m³
New Brunswick	OEL STEL (ppm)	15 ppm
New Brunswick	OEL TWA (mg/m³)	40 mg/m³
New Brunswick	OEL TWA (ppm)	10 ppm
New Foundland & Labrador	OEL TWA (ppm)	0.2 ppm
Nova Scotia	OEL TWA (ppm)	0.2 ppm
Nunavut	OEL STEL (ppm)	15 ppm
Nunavut	OEL TWA (ppm)	10 ppm

CLOVAMASTIC: LOW TEMPERATURE CURE EPOXY, BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

FURFURYL ALCOHOL (98-00-0)		
Northwest Territories	OEL STEL (ppm)	15 ppm
Northwest Territories	OEL TWA (ppm)	10 ppm
Ontario	OEL STEL (ppm)	15 ppm
Ontario	OEL TWA (ppm)	10 ppm
Prince Edward Island	OEL TWA (ppm)	0.2 ppm
Saskatchewan	OEL STEL (ppm)	15 ppm
Saskatchewan	OEL TWA (ppm)	10 ppm
Yukon	OEL STEL (mg/m³)	40 mg/m³
Yukon	OEL STEL (ppm)	10 ppm
Yukon	OEL TWA (mg/m³)	20 mg/m³
Yukon	OEL TWA (ppm)	5 ppm
M.E.K. (78-93-3)		
USA - ACGIH	ACGIH TWA (ppm)	200 ppm
USA - ACGIH	ACGIH STEL (ppm)	300 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m³)	590 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Canada (Quebec)	VECD (mg/m³)	300 mg/m³
Canada (Quebec)	VECD (ppm)	100 ppm
Canada (Quebec)	VEMP (mg/m³)	150 mg/m³
Canada (Quebec)	VEMP (ppm)	50 ppm
Alberta	OEL STEL (mg/m³)	885 mg/m³
Alberta	OEL STEL (ppm)	300 ppm
Alberta	OEL TWA (mg/m³)	590 mg/m³
Alberta	OEL TWA (ppm)	200 ppm
British Columbia	OEL STEL (ppm)	100 ppm
British Columbia	OEL TWA (ppm)	50 ppm
Manitoba	OEL STEL (ppm)	300 ppm
Manitoba	OEL TWA (ppm)	200 ppm
New Brunswick	OEL STEL (mg/m³)	885 mg/m³
New Brunswick	OEL STEL (ppm)	300 ppm
New Brunswick	OEL TWA (mg/m³)	590 mg/m³
New Brunswick	OEL TWA (ppm)	200 ppm
New Foundland & Labrador	OEL STEL (ppm)	300 ppm
New Foundland & Labrador	OEL TWA (ppm)	200 ppm
Nova Scotia	OEL STEL (ppm)	300 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nunavut	OEL STEL (ppm)	300 ppm
Nunavut	OEL TWA (ppm)	200 ppm
Northwest Territories	OEL STEL (ppm)	300 ppm
Northwest Territories	OEL TWA (ppm)	200 ppm
Ontario	OEL STEL (ppm)	300 ppm
Ontario	OEL TWA (ppm)	200 ppm
Prince Edward Island	OEL STEL (ppm)	300 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Saskatchewan	OEL STEL (ppm)	300 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Yukon	OEL STEL (mg/m³)	740 mg/m³
Yukon	OEL STEL (ppm)	250 ppm
Yukon	OEL TWA (mg/m³)	590 mg/m³
Yukon	OEL TWA (ppm)	200 ppm

CLOVAMASTIC: LOW TEMPERATURE CURE EPOXY, BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gas mask. Gloves. Protective clothing. Safety glasses.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Black.
Odor	: sharp
Odor threshold	: No data available
pH	: 7
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: -40 °C
Boiling point	: 79 - 218 °C
Flash point	: 20.5 °C SETAFLASH CLOSED CUP
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor pressure	: 77.5 mm Hg
Vapor pressure at 50 °C	: No data available
Specific gravity	: 1.63
Solubility	: Water: 1 %
Log Pow	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: LEL: 1.4 vol % UEL: 16.3 vol %

9.2. Other information

VOC content : < 124 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: Highly flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.
Incompatible materials	: acids. Oxidizing agent. Bases.

CLOVAMASTIC: LOW TEMPERATURE CURE EPOXY, BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Likely routes of exposure : Dermal. Inhalation. oral.

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

CARBON BLACK PIGMENT (1333-86-4)

LD50 oral rat	> 15400 mg/kg
---------------	---------------

Alkyl (C12-14) glycidyl ether (68609-97-2)

LD50 oral rat	17100 mg/kg
LD50 dermal rabbit	> 3987 mg/kg

FURFURYL ALCOHOL (98-00-0)

LD50 oral rat	110 mg/kg
LD50 dermal rabbit	657 mg/kg
LC50 inhalation rat (ppm)	233 ppm/4h

M.E.K. (78-93-3)

LD50 oral rat	2483 mg/kg
LD50 dermal rabbit	5000 mg/kg
LC50 inhalation rat (ppm)	11700 ppm/4h

Skin corrosion/irritation : Not classified
pH: 7

Serious eye damage/irritation : Not classified
pH: 7

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

CARBON BLACK PIGMENT (1333-86-4)

LC50 fish 1	> 1000 mg/l Brachydanio rerio
EC50 Daphnia 1	> 5600 mg/l
ErC50 (algae)	> 10000 mg/l Scenedesmus subspicatus

FURFURYL ALCOHOL (98-00-0)

LC50 fish 1	32 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
-------------	---

M.E.K. (78-93-3)

LC50 fish 1	3130 - 3320 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	> 520 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Daphnia 2	5091 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

CLOVAMASTIC: LOW TEMPERATURE CURE EPOXY, BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

M.E.K. (78-93-3)

Log Pow 0.3

12.4. Mobility in soil

M.E.K. (78-93-3)

Log Pow 0.3

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

UN-No. (TDG) : UN1263
Packing group : II - Medium Danger
TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids
Transport document description : UN1263 PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass), 3, II

Proper Shipping Name (Transportation of Dangerous Goods) : PAINT
including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass

Hazard labels (TDG) : 3 - Flammable liquids



TDG Special Provisions : 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (by dry mass).
142 - The following shipping names may be used to meet the requirements of Part 3 (Documentation) and Part 4 (Dangerous Goods Safety Marks) when these dangerous goods are offered for transport in the same means of containment: (a)"PAINT RELATED MATERIAL" may be used for a means of containment containing both paint and paint related material; (b)"PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" may be used for a means of containment containing both paint, corrosive, flammable, and paint related material, corrosive, flammable; (c)"PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" may be used for a means of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d)"PRINTING INK RELATED MATERIAL" may be used for a means of containment containing both printing ink and printing ink related material. SOR/2014-306

Explosive Limit and Limited Quantity Index : 5 L
Excepted quantities (TDG) : E2
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 5 L
Marine pollutant : Yes (IMDG only)



CLOVAMASTIC: LOW TEMPERATURE CURE EPOXY, BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

14.2. Transport information/DOT

Department of Transport

DOT NA no. : UN1263
UN-No.(DOT) : 1263
Packing group (DOT) : II - Medium Danger

Transport document description : UN1263 Paint, 3, II
Proper Shipping Name (DOT) : Paint
Contains Statement Field Selection (DOT) :

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Division (DOT) : 3
Hazard labels (DOT) : 3 - Flammable liquid



Dangerous for the environment : Yes
Marine pollutant : Yes



DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).

367 - For the purposes of documentation and package marking: a. The proper shipping name "Paint related material" may be used for consignments of packages containing "Paint" and "Paint related material" in the same package; b. The proper shipping name "Paint related material, corrosive, flammable" may be used for consignments of packages containing "Paint, corrosive, flammable" and "Paint related material, corrosive, flammable" in the same package; c. The proper shipping name "Paint related material, flammable, corrosive" may be used for consignments of packages containing "Paint, flammable, corrosive" and "Paint related material, flammable, corrosive" in the same package; and d. The proper shipping name "Printing ink related material" may be used for consignments of packages containing "Printing ink" and "Printing ink related material" in the same package.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

CLOVAMASTIC: LOW TEMPERATURE CURE EPOXY, BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

14.3. Air and sea transport

IMDG

UN-No. (IMDG) : 1263
Proper Shipping Name (IMDG) : PAINT
Transport document description (IMDG) : UN 1263 PAINT, 3, II
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : II - substances presenting medium danger

IATA

UN-No. (IATA) : 1263
Proper Shipping Name (IATA) : Paint
Transport document description (IATA) : UN 1263 Paint, 3, II
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. National regulations

CARBON BLACK PIGMENT (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Alkyl (C12-14) glycidyl ether (68609-97-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

FURFURYL ALCOHOL (98-00-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

M.E.K. (78-93-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

15.2. International regulations

CARBON BLACK PIGMENT (1333-86-4)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.
Listed on European List of Notified Chemical Substances (ELINCS)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Alkyl (C12-14) glycidyl ether (68609-97-2)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

CLOVAMASTIC: LOW TEMPERATURE CURE EPOXY, BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

FURFURYL ALCOHOL (98-00-0)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

M.E.K. (78-93-3)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Poisonous and Deleterious Substances Control Law
Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16: Other information

SDS Major/Minor : None
Date of issue : 07/25/2016
Revision date : 07/31/2018
Supersedes : 12/08/2016

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H227	Combustible liquid
H301	Toxic if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects

SDS Canada (GHS) - Cloverdale

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Cloverdale Paint Inc. to be accurate. No warranty concerning the accuracy of these sources is made and Cloverdale Paint Inc. will not be held liable for claims relating to use of this information or recommendations.