

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
 Product name : ARMOURSHIELD 839: HIGH GLOSS, JET BLACK
 Product code : 83948A
 Product group : Trade product

1.2. Recommended use and restrictions on use

Recommended use : Coatings and paints

1.3. Supplier

Cloverdale Paint Inc.
 400- 2630 Croydon Drive
 V3Z 6T3 Surrey - CANADA
 T 1-(604)-596-6261
btinsley@cloverdalepaint.com - www.cloverdalepaint.com

1.4. Emergency telephone number

Emergency number : CANUTEC 24 hr. Emergency Number (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Flammable liquids Category 2 H225
 Acute toxicity (inhalation:vapour) Category 3 H331
 Serious eye damage/eye irritation Category 2 H319
 Germ cell mutagenicity, Category 1 H340
 Carcinogenicity, Category 1 H350
 Specific target organ toxicity (single exposure) Category 3 H336
 Hazardous to the aquatic environment - Acute Hazard Category 3 H402
 Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-CA labeling

Hazard pictograms (GHS-CA) :



GHS02



GHS06



GHS07



GHS08

Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) : H225 - Highly flammable liquid and vapour
 H319 - Causes serious eye irritation
 H331 - Toxic if inhaled
 H336 - May cause drowsiness or dizziness
 H340 - May cause genetic defects
 H350 - May cause cancer
 H402 - Harmful to aquatic life

Precautionary statements (GHS-CA) : P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/bond container and receiving equipment.
 P241 - Use explosion-proof electrical, ventilating, lighting equipment
 P261 - Avoid breathing mist, vapors, spray.
 P264 - Wash Skin thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P273 - Avoid release to the environment.
 P280 - Wear eye protection, face protection, protective gloves, protective clothing.
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with soap and water .

ARMOURSHIELD 839: HIGH GLOSS, JET BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P370+P378 - In case of fire: Use carbon dioxide (CO₂), foam, dry chemical to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
EEP (2-ETHOXYETHYL PROPIONATE)	Ethyl 3-ethoxypropionate / Propanoic acid, 3-ethoxy-, ethyl ester / Propionate, 3-ethoxy-, ethyl / Propionic acid, 3-ethoxy-, ethyl ester / EEP solvent / 3-Ethoxypropionic acid, ethyl ester / Ethyl .beta.-ethoxypropionate	(CAS-No.) 763-69-9	16	Flam. Liq. 3, H226 Acute Tox. 3 (Inhalation:vapour), H331 Aquatic Acute 3, H402
METHYL ACETATE - HIGH PURITY	Acetate, methyl / Acetic acid, methyl ester / Methyl ethanoate / METHYL ACETATE	(CAS-No.) 79-20-9	15.2	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
N-BUTYL ACETATE - BULK	1-Butyl acetate / Butyl acetate, n- / Normal butyl acetate / Butyl acetate / BUTYL ACETATE / Acetic acid, n-butyl ester / Acetic acid, butyl ester / Butyl ethanoate	(CAS-No.) 123-86-4	11.8	Flam. Liq. 2, H225 Acute Tox. 2 (Inhalation), H330 STOT SE 3, H336 Aquatic Acute 3, H402
EB ACETATE	Acetate, 2-butoxyethyl / Acetic acid, 2-butoxyethyl ester / 2-Butoxyethanol acetate / 2-Butoxyethyl acetate / Butyl glycol acetate / Ethanol, 2-butoxy-, acetate / Ethylene glycol butyl ether acetate / Butoxyethyl acetate, 2- / Ethanol, 2-butoxy-, 1-acetate / BUTOXYETHYL ACETATE / Butoxyethyl acetate / EGBEA / Butyl Cellosolve acetate / Butyl cellosolve acetate	(CAS-No.) 112-07-2	1.8	Flam. Liq. 4, H227 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
CARBON BLACK	C.I. 77266 / C.I. Pigment Black 6 / C.I. Pigment Black 7 / Carbon blacks / Lampblack / CI 77266 / Vegetable carbon / Microjet Black CW / Pigment Black 7 / Coal soot / Coal soots / Channel black / Bonjet Black CW / Carbon Black	(CAS-No.) 1333-86-4	1.4	Carc. 2, H351 Comb. Dust
Solvent naphtha (petroleum), light aliphatic	Solvent naphtha (petroleum), light aliphatic / Naphtha, petroleum, light aliphatic / Solvent naphtha light aliphatic / Naphtha, light aliphatic solvent / Light aliphatic solvent naphtha (petroleum) / Solvent naphtha (petroleum), light aliphatic - low boiling point naphtha / Aliphatic light naphtha / Solvent naphtha(petroleum), light aliphatic / Solvent naphtha, petroleum, light aliphatic (A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C5-10 and boiling in the range of approximately 35-160°C.) / Light aliphatic solvent naphtha	(CAS-No.) 64742-89-8	1.2	Flam. Liq. 1, H224 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304

ARMOURSHIELD 839: HIGH GLOSS, JET BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
2,4-PENTANEDIONE	Acetoacetone / Acetone, acetyl- / Acetyl 2-propanone / Acetyl acetone / Acetylacetone / Diacetylmethane / Pentane-2,4-dione / Pentan-2,4-dione / 2,4-Pentandione / Pentadione, 2,4-	(CAS-No.) 123-54-6	1.2	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Aquatic Acute 3, H402
Solvent naphtha, petroleum, light aromatic	Solvent naphtha (petroleum), light aromatic / Light aromatic solvent naphtha / Aromatic 100 / Solvent naphtha, petroleum, light aromatic-low boiling point hydrogen treated naphtha / Light aromatic solvent naphtha (petroleum) (C8-10) / Solvent naphtha, petroleum, light aromatic (A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8-10 and boiling in the range of approximately 135-210°C.) / Aromatic naphtha, type I / Solvent naphtha (petroleum), light aromatic, hydrotreated	(CAS-No.) 64742-95-6	0.1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Take medical advice.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause moderate irritation. Repeated or prolonged contact may cause sensitization of the skin (dermatitis, reddening,...).
Symptoms/effects after eye contact	: May cause severe irritation.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Dry chemical. Foam. Carbon dioxide.
------------------------------	---------------------------------------

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	: Do not use a heavy water stream.
--------------------------------	------------------------------------

5.3. Specific hazards arising from the hazardous product

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Eliminate all ignition sources if safe to do so. Evacuate area. Exercise caution when fighting any chemical fire. Use extinguishing agent suitable for surrounding fire. Use water spray or fog for cooling exposed containers. Wear personal protective equipment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid contact with skin and eyes. Avoid inhalation of vapor and spray mist. Eliminate every possible source of ignition. Evacuate area. Ground and bond container and receiving equipment. Ventilate area. Wear personal protective equipment. Soak up with absorbent material (for example sand, sawdust, neutral absorbent granule, silica gel).
------------------	--

ARMOURSHIELD 839: HIGH GLOSS, JET BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

6.2. Methods and materials for containment and cleaning up

- For containment : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect spillage. Dispose of contaminated materials in accordance with current regulations.
- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8 "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid breathing mist, vapors, spray.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
- Additional hazards when processed : Avoid breathing dust, mist or spray. Avoid contact with skin and eyes. Ensure good ventilation of the work station. Ground and bond container and receiving equipment. Handle carefully.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment. Keep container closed when not in use. Provide local exhaust or general room ventilation. Use only non-sparking tools.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Incompatible products : Oxidizing agent. acids. Bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

CARBON BLACK (1333-86-4)		
USA - ACGIH	ACGIH TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
USA - OSHA	OSHA PEL (TWA) (mg/m³)	3.5 mg/m³
Canada (Quebec)	VEMP (mg/m³)	3.5 mg/m³
Alberta	OEL TWA (mg/m³)	3.5 mg/m³
British Columbia	OEL TWA (mg/m³)	3 mg/m³ (inhalable)
Manitoba	OEL TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m³)	3.5 mg/m³
New Foundland & Labrador	OEL TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
Nunavut	OEL STEL (mg/m³)	7 mg/m³
Nunavut	OEL TWA (mg/m³)	3.5 mg/m³
Northwest Territories	OEL STEL (mg/m³)	7 mg/m³
Northwest Territories	OEL TWA (mg/m³)	3.5 mg/m³
Ontario	OEL TWA (mg/m³)	3 mg/m³ (inhalable)
Prince Edward Island	OEL TWA (mg/m³)	3 mg/m³ (inhalable particulate matter)
Saskatchewan	OEL STEL (mg/m³)	7 mg/m³
Saskatchewan	OEL TWA (mg/m³)	3.5 mg/m³
Yukon	OEL STEL (mg/m³)	7 mg/m³
Yukon	OEL TWA (mg/m³)	3.5 mg/m³
EEP (2-ETHOXYETHYL PROPIONATE) (763-69-9)		
Ontario	OEL TWA (mg/m³)	300 mg/m³
Ontario	OEL TWA (ppm)	50 ppm

ARMOURSHIELD 839: HIGH GLOSS, JET BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2,4-PENTANEDIONE (123-54-6)		
USA - ACGIH	ACGIH TWA (ppm)	25 ppm
USA - ACGIH	Remark (ACGIH)	Neurotoxicity; CNS impair
Manitoba	OEL TWA (ppm)	25 ppm
New Foundland & Labrador	OEL TWA (ppm)	25 ppm
Nova Scotia	OEL TWA (ppm)	25 ppm
Ontario	OEL TWA (ppm)	25 ppm
Prince Edward Island	OEL TWA (ppm)	25 ppm
N-BUTYL ACETATE - BULK (123-86-4)		
USA - ACGIH	ACGIH TWA (ppm)	150 ppm
USA - ACGIH	ACGIH STEL (ppm)	200 ppm
USA - ACGIH	Remark (ACGIH)	Eye & URT irr
USA - OSHA	OSHA PEL (TWA) (mg/m³)	710 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	150 ppm
Canada (Quebec)	VECD (mg/m³)	950 mg/m³
Canada (Quebec)	VECD (ppm)	200 ppm
Canada (Quebec)	VEMP (mg/m³)	713 mg/m³
Canada (Quebec)	VEMP (ppm)	150 ppm
Alberta	OEL STEL (mg/m³)	950 mg/m³
Alberta	OEL STEL (ppm)	200 ppm
Alberta	OEL TWA (mg/m³)	713 mg/m³
Alberta	OEL TWA (ppm)	150 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL STEL (ppm)	150 ppm
Manitoba	OEL TWA (ppm)	50 ppm
New Brunswick	OEL STEL (mg/m³)	950 mg/m³
New Brunswick	OEL STEL (ppm)	200 ppm
New Brunswick	OEL TWA (mg/m³)	713 mg/m³
New Brunswick	OEL TWA (ppm)	150 ppm
New Foundland & Labrador	OEL STEL (ppm)	150 ppm
New Foundland & Labrador	OEL TWA (ppm)	50 ppm
Nova Scotia	OEL STEL (ppm)	150 ppm
Nova Scotia	OEL TWA (ppm)	50 ppm
Nunavut	OEL STEL (ppm)	200 ppm
Nunavut	OEL TWA (ppm)	150 ppm
Northwest Territories	OEL STEL (ppm)	200 ppm
Northwest Territories	OEL TWA (ppm)	150 ppm
Ontario	OEL STEL (ppm)	200 ppm
Ontario	OEL TWA (ppm)	150 ppm
Prince Edward Island	OEL STEL (ppm)	150 ppm
Prince Edward Island	OEL TWA (ppm)	50 ppm
Saskatchewan	OEL STEL (ppm)	200 ppm
Saskatchewan	OEL TWA (ppm)	150 ppm
Yukon	OEL STEL (mg/m³)	950 mg/m³
Yukon	OEL STEL (ppm)	200 ppm
Yukon	OEL TWA (mg/m³)	710 mg/m³
Yukon	OEL TWA (ppm)	150 ppm
METHYL ACETATE - HIGH PURITY (79-20-9)		
USA - ACGIH	ACGIH TWA (ppm)	200 ppm
USA - ACGIH	ACGIH STEL (ppm)	250 ppm

ARMOURSHIELD 839: HIGH GLOSS, JET BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

METHYL ACETATE - HIGH PURITY (79-20-9)		
USA - ACGIH	Remark (ACGIH)	eye & URT irr
USA - OSHA	OSHA PEL (TWA) (mg/m³)	610 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Canada (Quebec)	VECD (mg/m³)	757 mg/m³
Canada (Quebec)	VECD (ppm)	250 ppm
Canada (Quebec)	VEMP (mg/m³)	606 mg/m³
Canada (Quebec)	VEMP (ppm)	200 ppm
Alberta	OEL STEL (mg/m³)	757 mg/m³
Alberta	OEL STEL (ppm)	250 ppm
Alberta	OEL TWA (mg/m³)	606 mg/m³
Alberta	OEL TWA (ppm)	200 ppm
British Columbia	OEL STEL (ppm)	250 ppm
British Columbia	OEL TWA (ppm)	200 ppm
Manitoba	OEL STEL (ppm)	250 ppm
Manitoba	OEL TWA (ppm)	200 ppm
New Brunswick	OEL STEL (mg/m³)	757 mg/m³
New Brunswick	OEL STEL (ppm)	250 ppm
New Brunswick	OEL TWA (mg/m³)	606 mg/m³
New Brunswick	OEL TWA (ppm)	200 ppm
New Foundland & Labrador	OEL STEL (ppm)	250 ppm
New Foundland & Labrador	OEL TWA (ppm)	200 ppm
Nova Scotia	OEL STEL (ppm)	250 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nunavut	OEL STEL (ppm)	250 ppm
Nunavut	OEL TWA (ppm)	200 ppm
Northwest Territories	OEL STEL (ppm)	250 ppm
Northwest Territories	OEL TWA (ppm)	200 ppm
Ontario	OEL STEL (ppm)	250 ppm
Ontario	OEL TWA (ppm)	200 ppm
Prince Edward Island	OEL STEL (ppm)	250 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Saskatchewan	OEL STEL (ppm)	250 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Yukon	OEL STEL (mg/m³)	760 mg/m³
Yukon	OEL STEL (ppm)	250 ppm
Yukon	OEL TWA (mg/m³)	610 mg/m³
Yukon	OEL TWA (ppm)	200 ppm
EB ACETATE (112-07-2)		
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
Alberta	OEL TWA (mg/m³)	131 mg/m³
Alberta	OEL TWA (ppm)	20 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Foundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (ppm)	30 ppm
Nunavut	OEL TWA (ppm)	20 ppm
Northwest Territories	OEL STEL (ppm)	30 ppm
Northwest Territories	OEL TWA (ppm)	20 ppm
Ontario	OEL TWA (ppm)	20 ppm

ARMOURSHIELD 839: HIGH GLOSS, JET BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

EB ACETATE (112-07-2)

Prince Edward Island	OEL TWA (ppm)	20 ppm
Saskatchewan	OEL STEL (ppm)	30 ppm
Saskatchewan	OEL TWA (ppm)	20 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gas mask. Gloves. Protective clothing. Safety glasses.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Black.
Odor	: aromatic
Odor threshold	: No data available
pH	: 7
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: -40 °C
Boiling point	: 57 - 192 °C
Flash point	: 7 °C SETAFLASH CLOSED CUP
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor pressure	: 173 mm Hg
Vapor pressure at 50 °C	: No data available
Specific gravity	: 1.01
Solubility	: Water: 16 %
Log Pow	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: LEL: 0.5 vol % UEL: 36 vol %

9.2. Other information

VOC content : 411 g/l

ARMOURSHIELD 839: HIGH GLOSS, JET BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: Highly flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.
Incompatible materials	: acids. Oxidizing agent. Bases.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Likely routes of exposure	: Dermal. Inhalation. oral.
---------------------------	-----------------------------

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Inhalation:vapour: Toxic if inhaled.

ATE CA (vapours)	3.443 mg/l/4h
------------------	---------------

CARBON BLACK (1333-86-4)

LD50 oral rat	> 15400 mg/kg
---------------	---------------

EEP (2-ETHOXYETHYL PROPIONATE) (763-69-9)

LD50 oral rat	5 g/kg
LD50 dermal rabbit	> 9500 mg/kg
LC50 inhalation rat (mg/l)	> 5.96 mg/l (Exposure time: 6 h)

2,4-PENTANEDIONE (123-54-6)

LD50 oral rat	760 mg/kg
LD50 dermal rabbit	1370 mg/kg
LC50 inhalation rat (ppm)	1224 ppm/4h

N-BUTYL ACETATE - BULK (123-86-4)

LD50 oral rat	10768 mg/kg
LD50 dermal rabbit	> 17600 mg/kg
LC50 inhalation rat (ppm)	390 ppm/4h

METHYL ACETATE - HIGH PURITY (79-20-9)

LD50 oral rat	> 5 g/kg
LD50 dermal rabbit	> 5 g/kg
LC50 inhalation rat (mg/l)	> 49000 mg/m ³ (Exposure time: 4 h)

EB ACETATE (112-07-2)

LD50 oral rat	2400 mg/kg
LD50 dermal rabbit	1500 mg/kg
LC50 inhalation rat (ppm)	> 400 ppm/4h

Solvent naphtha (petroleum), light aliphatic (64742-89-8)

LD50 dermal rabbit	3000 mg/kg
--------------------	------------

Solvent naphtha, petroleum, light aromatic (64742-95-6)

LD50 oral rat	8400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (ppm)	3400 ppm/4h

Skin corrosion/irritation	: Not classified pH: 7
Serious eye damage/irritation	: Causes serious eye irritation. pH: 7
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness.

ARMOURSHIELD 839: HIGH GLOSS, JET BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life.

EEP (2-ETHOXYETHYL PROPIONATE) (763-69-9)	
LC50 fish 1	62 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	970 mg/l (Exposure time: 48 h - Species: Daphnia magna)
2,4-PENTANEDIONE (123-54-6)	
LC50 fish 1	98.3 - 110 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	50.3 - 71.8 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
EC50 Daphnia 1	34.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
N-BUTYL ACETATE - BULK (123-86-4)	
LC50 fish 1	100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 fish 2	17 - 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
METHYL ACETATE - HIGH PURITY (79-20-9)	
LC50 fish 1	295 - 348 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	250 - 350 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	1026.7 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EB ACETATE (112-07-2)	
LC50 fish 1	20 - 40 mg/l RAINBOW TROUT
EC50 Daphnia 1	37 mg/l (Exposure time: 48 h - Species: Daphnia magna)
ErC50 (algae)	1570 mg/l PSEUDOKIRCHNERIELLA SUBCAPITATA
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LC50 fish 1	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

EEP (2-ETHOXYETHYL PROPIONATE) (763-69-9)	
Log Pow	1.35
2,4-PENTANEDIONE (123-54-6)	
Log Pow	0.34
N-BUTYL ACETATE - BULK (123-86-4)	
Log Pow	1.81 (at 23 °C)
METHYL ACETATE - HIGH PURITY (79-20-9)	
Log Pow	0.18
EB ACETATE (112-07-2)	
BCF fish 1	(no significant bioaccumulation)
Log Pow	1.51

12.4. Mobility in soil

EEP (2-ETHOXYETHYL PROPIONATE) (763-69-9)	
Log Pow	1.35
2,4-PENTANEDIONE (123-54-6)	
Log Pow	0.34
N-BUTYL ACETATE - BULK (123-86-4)	
Log Pow	1.81 (at 23 °C)
METHYL ACETATE - HIGH PURITY (79-20-9)	
Log Pow	0.18
EB ACETATE (112-07-2)	
Log Pow	1.51

ARMOURSHIELD 839: HIGH GLOSS, JET BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapors may accumulate in the container.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

UN-No. (TDG)	: UN1263
Packing group	: II - Medium Danger
TDG Primary Hazard Classes	: 3 - Class 3 - Flammable Liquids
Transport document description	: UN1263 PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass), 3, II
Proper Shipping Name (Transportation of Dangerous Goods)	: PAINT including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass
Hazard labels (TDG)	: 3 - Flammable liquids



TDG Special Provisions	: 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (by dry mass). 142 - The following shipping names may be used to meet the requirements of Part 3 (Documentation) and Part 4 (Dangerous Goods Safety Marks) when these dangerous goods are offered for transport in the same means of containment: (a)"PAINT RELATED MATERIAL" may be used for a means of containment containing both paint and paint related material; (b)"PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" may be used for a means of containment containing both paint, corrosive, flammable, and paint related material, corrosive, flammable; (c)"PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" may be used for a means of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d)"PRINTING INK RELATED MATERIAL" may be used for a means of containment containing both printing ink and printing ink related material. SOR/2014-306
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E2
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 5 L

14.2. Transport information/DOT

Department of Transport

DOT NA no.	: UN1263
UN-No.(DOT)	: 1263
Packing group (DOT)	: II - Medium Danger
Transport document description	: UN1263 Paint, 3, II
Proper Shipping Name (DOT)	: Paint
Contains Statement Field Selection (DOT)	:
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

ARMOURSHIELD 839: HIGH GLOSS, JET BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Division (DOT) : 3
Hazard labels (DOT) : 3 - Flammable liquid



Dangerous for the environment : No

DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).
367 - For the purposes of documentation and package marking: a. The proper shipping name "Paint related material" may be used for consignments of packages containing "Paint" and "Paint related material" in the same package; b. The proper shipping name "Paint related material, corrosive, flammable" may be used for consignments of packages containing "Paint, corrosive, flammable" and "Paint related material, corrosive, flammable" in the same package; c. The proper shipping name "Paint related material, flammable, corrosive" may be used for consignments of packages containing "Paint, flammable, corrosive" and "Paint related material, flammable, corrosive" in the same package; and d. The proper shipping name "Printing ink related material" may be used for consignments of packages containing "Printing ink" and "Printing ink related material" in the same package.
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

14.3. Air and sea transport

IMDG

UN-No. (IMDG) : 1263
Proper Shipping Name (IMDG) : PAINT
Transport document description (IMDG) : UN 1263 PAINT, 3, II
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : II - substances presenting medium danger

IATA

UN-No. (IATA) : 1263
Proper Shipping Name (IATA) : Paint
Transport document description (IATA) : UN 1263 Paint, 3, II

ARMOURSHIELD 839: HIGH GLOSS, JET BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. National regulations

CARBON BLACK (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EEP (2-ETHOXYETHYL PROPIONATE) (763-69-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

2,4-PENTANEDIONE (123-54-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

N-BUTYL ACETATE - BULK (123-86-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

METHYL ACETATE - HIGH PURITY (79-20-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EB ACETATE (112-07-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Solvent naphtha (petroleum), light aliphatic (64742-89-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Solvent naphtha, petroleum, light aromatic (64742-95-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

15.2. International regulations

CARBON BLACK (1333-86-4)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.
Listed on European List of Notified Chemical Substances (ELINCS)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

EEP (2-ETHOXYETHYL PROPIONATE) (763-69-9)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

2,4-PENTANEDIONE (123-54-6)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

ARMOURSHIELD 839: HIGH GLOSS, JET BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

N-BUTYL ACETATE - BULK (123-86-4)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

METHYL ACETATE - HIGH PURITY (79-20-9)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

EB ACETATE (112-07-2)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Solvent naphtha (petroleum), light aliphatic (64742-89-8)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Solvent naphtha, petroleum, light aromatic (64742-95-6)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16: Other information

SDS Major/Minor : None
Date of issue : 11/17/2016
Revision date : 01/17/2019
Supersedes : 11/17/2016

Full text of H-phrases:

H224	Extremely flammable liquid and vapour
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H330	Fatal if inhaled

ARMOURSHIELD 839: HIGH GLOSS, JET BLACK

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

H331	Toxic if inhaled
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

SDS Canada (GHS) - Cloverdale

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Cloverdale Paint Inc. to be accurate. No warranty concerning the accuracy of these sources is made and Cloverdale Paint Inc. will not be held liable for claims relating to use of this information or recommendations.